

BR2300-PLN6

BR2300 DIP SWITCHES SETTING : (MDB/ICT-BC/ccTalk)

Supported bill PLN 10, 20, 50, 100, 200, 500 6 bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	Reject PLN 10 & 20	ON									
★	Accept PLN 10 & 20	OFF									
★	Reject PLN 50 & 100		ON								
★	Accept PLN 50 & 100		OFF								
★	Reject PLN 200 & 500			ON							
★	Accept PLN 200 & 500			OFF							
★	High Acceptance (Note.3)				ON						
★	High Security				OFF						
★	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	(MDB only)			ON						
★	Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0				OFF						
★	Normal					OFF	OFF				
	Load Banknote to Recycle					ON	OFF				
	Load Banknote to Stacker					OFF	ON				
	Unload Banknote to Stacker					ON	ON				
★	ccTalk							ON	OFF		
	ccTalk (Note.1)							OFF	ON		
★	MDB Mode							OFF	OFF		
★	ICT-BC Mode							ON	ON		
	ccTalk	MDB Mode			ICT-BC Mode						
★	Encryption MODE	★ Virtual MDB Recycler Function (Note.2)			Connect with MDB Connector					ON	
	Decrypt MODE	Standard MDB Recycler Function			★ Connect with RS232 Connector					OFF	

★ Manufacture setting

After setting dip switch of the credit pulses, you should reset the bill acceptor again.

Note.1: Turn this dip to with restart the bill acceptor will restore ccTalk address to its default value of 40 and the encryption key to its default value of 123456.

Note.2: Recycled Banknote represents virtual MDB coin type.

Note.3: High acceptance mode will increase accepting rate, however, it will reduce the security level of Bill Acceptor.

Note.4: Calibrate card is needed.

BR2300-PLN6(MDB/ICT-BC/ccTalk)

Currency Assign Data

Interface Bill value	ccTalk	ICT-BC	MDB	Recycler banknote inventory	
BV1	PLN 10	PLN 10	PLN 10	PLN 10	50 pcs
BV2	PLN 20	PLN 20	PLN 20	PLN 20	45 pcs
BV3	PLN 50	PLN 50	PLN 50	PLN 50	45 pcs
BV4	PLN 100	PLN 100	PLN 100	PLN 100	45 pcs
BV5	PLN 200	PLN 200	PLN 200	PLN 200	45 pcs
BV6	PLN 500	PLN 500	PLN 500	PLN 500	40 pcs