



BGL5

L83 DIP SWITCHES SETTING : 1(Pulse/ MDB)

Supported bill BGL 5, 10, 20, 50, 100 5bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / BGL 5	OFF	OFF	OFF							
	2 Pulse / BGL 5	OFF	OFF	ON							
	3 Pulse / BGL 5	OFF	ON	OFF							
	4 Pulse / BGL 5	OFF	ON	ON							
	5 Pulse / BGL 5	ON	OFF	OFF							
	10 Pulse / BGL 5	ON	OFF	ON							
	20 Pulse / BGL 5	ON	ON	OFF							
	100 Pulse / BGL 5	ON	ON	ON							
	Fast output Pulse <small>Lo= 50ms Hi=100ms</small>				ON						
★	Slow output Pulse <small>Lo= 50ms Hi=300ms</small>				OFF						
	Inhibit level Active Low				ON						
★	Inhibit level Active High				OFF						
★	Accept BGL 5				ON						
	Reject BGL 5				OFF						
★	Accept BGL 10				ON						
	Reject BGL 10				OFF						
★	Accept BGL 20				ON						
	Reject BGL 20				OFF						
★	Accept BGL 50				ON						
	Reject BGL 50				OFF						
★	Accept BGL 100				ON						
	Reject BGL 100				OFF						

★ Manufacture setting

Note:(1)Please reset the bill acceptor after set the dip switch.

(2)Dip switches 1 to 5 are only used for pulse protocol.

DIP SWITCHES SETTING : 2(Pulse)

	FUNCTION	SW1	SW2	SW3	SW4
★	Pulse Normal High	ON			
	Pulse Normal Low	OFF			
★	Pulse Mode		ON		
	MDB Mode		OFF		
★	Reserved			ON	
				OFF	
★					ON
					OFF

★ Manufacture setting

DIP SWITCHES SETTING : 3(MDB)

	FUNCTION	SW1	SW2	SW3	SW4
★	Scaling Factor (SF) = 100	ON			
	Decimal Point Position (DPP) = 2	OFF			
	Scaling Factor (SF) = 1		ON		
	Decimal Point Position (DPP) = 0		OFF		
★	Pulse Mode		ON		
	MDB Mode		OFF		
★	Reserved			ON	
				OFF	
★					ON
					OFF

★ Manufacture setting