

## L83-BGN5

### L83 DIP SWITCHES SETTING : 1(Pulse/ICT104/MDB)

Supported bill BGN 5, 10, 20, 50, 100 5bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / BGN 5	OFF	OFF	OFF							
	2 Pulse / BGN 5	OFF	OFF	ON							
	3 Pulse / BGN 5	OFF	ON	OFF							
	4 Pulse / BGN 5	OFF	ON	ON							
	5 Pulse / BGN 5	ON	OFF	OFF							
	10 Pulse / BGN 5	ON	OFF	ON							
	20 Pulse / BGN 5	ON	ON	OFF							
	100 Pulse / BGN 5	ON	ON	ON							
	Fast output Pulse Lo= 50ms Hi=100ms				ON						
★	Slow output Pulse Lo= 50ms Hi=300ms				OFF						
	Inhibit level Active Low				ON						
★	Inhibit level Active High				OFF						
★	Accept BGN 5				ON						
	Reject BGN 5				OFF						
★	Accept BGN 10				ON						
	Reject BGN 10				OFF						
★	Accept BGN 20				ON						
	Reject BGN 20				OFF						
★	Accept BGN 50				ON						
	Reject BGN 50				OFF						
★	Accept BGN 100				ON						
	Reject BGN 100				OFF						

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

## L83-BGN5(Pulse/ICT104/MDB)

### DIP SWITCHES SETTING : 2(Pulse) Currency Assign Data

	FUNCTION	SW1	SW2	SW3	SW4
★	Pulse Normal High	ON			
	Pulse Normal Low	OFF			
★	Pulse Mode		ON	OFF	
	ICT104 Interface		OFF	ON	
	MDB Mode		ON	ON	
	Reserved		OFF	OFF	
★	Reserved				ON
					OFF

★ Manufacture setting

Interface Bill value	Pulse	ICT104	MDB
BV1	BGN 5	BGN 5	BGN 5
BV2	BGN 10	BGN 10	BGN 10
BV3	BGN 20	BGN 20	BGN 20
BV4	BGN 50	BGN 50	BGN 50
BV5	BGN 100	BGN 100	BGN 100

### DIP SWITCHES SETTING : 2(ICT104)

	FUNCTION	SW1	SW2	SW3	SW4
★	Reserved	ON			
		OFF			
	Pulse Mode		ON	OFF	
★	ICT104 Interface		OFF	ON	
	MDB Mode		ON	ON	
	Reserved		OFF	OFF	
★	Reserved				ON
					OFF

★ Manufacture setting

### DIP SWITCHES SETTING : 2(MDB)

	FUNCTION	SW1	SW2	SW3	SW4
★	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
	Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
	Pulse Mode		ON	OFF	
	ICT104 Interface		OFF	ON	
★	MDB Mode		ON	ON	
	Reserved		OFF	OFF	
★	Reserved				ON
					OFF

★ Manufacture setting