

## L83-RON7

### L83 Option Switch Settings : 1(Pulse/MDB/Parallel A5)

Supported bill RON 5, 10, 20, 50, 100, 200, 500 7bills.

L83 dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★ 1 Pulse / RON 5	OFF	OFF	OFF							
2 Pulses / RON 5	OFF	OFF	ON							
3 Pulses / RON 5	OFF	ON	OFF							
4 Pulses / RON 5	OFF	ON	ON							
5 Pulses / RON 5	ON	OFF	OFF							
10 Pulses / RON 5	ON	OFF	ON							
20 Pulses / RON 5	ON	ON	OFF							
100 Pulses / RON 5	ON	ON	ON							
Fast output Pulse <small>Lo= 85ms Hi=100ms</small>										
★ Slow output Pulse <small>Lo=150ms Hi=100ms</small>				OFF						
Inhibit level Active Low				ON						
★ Inhibit level Active High				OFF						
★ Accept RON 5				ON						
Reject RON 5				OFF						
★ Accept RON 10 & 20				ON						
Reject RON 10 & 20				OFF						
★ Accept RON 50				ON						
Reject RON 50				OFF						
★ Accept RON 100				ON						
Reject RON 100				OFF						
★ Accept RON 200 & 500				ON						
Reject RON 200 & 500				OFF						

◆ Manufacture Default setting.

Note.1 Please reset the bill acceptor after any changes on Dip switch.

Note.2 Dip Switch 1 to 5 are only for Pulse mode.

## L83-RON7(Pulse/MDB/Parallel A5)

### Interface Settings: 2(Pulse)

INTERFACE	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
Credit-Pulse Normal LOW	OFF			
★ Pulse Interface		ON	OFF	
Parallel A5 Interface		ON	ON	
MDB Interface		OFF	OFF	
Reserved		OFF	ON	
★ Reserved				ON
				OFF

★ Manufacture setting

### Interface Settings: 2(Parallel A5)

INTERFACE	SW1	SW2	SW3	SW4
★ Reserved	ON			
	OFF			
Pulse Interface		ON	OFF	
★ Parallel A5 Interface		ON	ON	
MDB Interface		OFF	OFF	
Reserved		OFF	ON	
★ Reserved				ON
				OFF

★ Manufacture setting

### Currency Assign Data

Interface Bill value	Pulse	MDB	Parallel A5
BV1	RON 5	RON 5	RON 5
BV2	RON 10	RON 10	RON 10
BV3	RON 50	RON 50	RON 50
BV4	RON 100	RON 100	RON 100
BV5	RON 200	RON 200	
BV6	RON 500	RON 500	
BV7	RON 20	RON 20	

### Interface Settings: 2(MDB)

INTERFACE	SW1	SW2	SW3	SW4
★ Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
Pulse Interface		ON	OFF	
Parallel A5 Interface		ON	ON	
★ MDB Interface		OFF	OFF	
Reserved		OFF	ON	
★ Reserved				ON
				OFF

★ Manufacture setting