L83-RON8

L83/P3/P6 DIP SWITCHES SETTING: 1(Special Pulse/RS232 A0/RS232 A1)

Supported bill RON 1, 5, 10, 20, 50, 100, 200, 500 8 bills.

| | FUNCTION | SW1 | SW2 | SW3 | SW4 | SW5 | SW6 | SW7 | SW8 | SW9 | SW10 |
|---|---------------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|
| * | 1 Pulse / RON 1 | OFF | OFF | | | | | | | | |
| | 2 Pulses / RON 1 | OFF | ON | | | | | | | | |
| | 5 Pulses / RON 1 | ON | OFF | | | | | | | | |
| | 20 Pulses / RON 1 | ON | ON | | | | | | | | |
| * | Lo= 50 Hi=100 | | | OFF | OFF | | | | | | |
| | Lo= 85 Hi=100 | | | OFF | ON | | | | | | |
| | Lo=100 Hi=100 | | | ON | OFF | | | | | | |
| | Lo=150 Hi=100 | | | ON | ON | | | | | | |
| | Inhibit level Active Low | | | | | ON | | | | | |
| * | Inhibit level Active High | | | | | OFF | | | | | |
| * | Accept RON 1 | | | | | | ON | | | | |
| | Reject RON 1 | | | | | | OFF | | | | |
| * | Accept RON 5 | | | | | | | ON | | | |
| | Reject RON 5 | | | | | | | OFF | | | |
| * | Accept RON 10 & 20 | | | | | | | | ON | | |
| | Reject RON 10 & 20 | | | | | | | | OFF | | |
| * | Accept RON 50 & 100 | | | | | | | | | ON | |
| | Reject RON 50 & 100 | | | | | | | | | OFF | |
| k | Accept RON 200 & 500 | | | | | | | | | | ON |
| | Reject RON 200 & 500 | | | | | | | | | | OFF |

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

Currency Assign Data

| Interface Bill value | Pulse | RS232 A0 | RS232 A1 | Interface Bill value | Pulse | RS232 A0 | RS232 A1 |
|-------------------------|--------|----------|----------|-------------------------|---------|----------|----------|
| BV1 | RON 1 | RON 1 | RON 1 | BV5 | RON 100 | RON 100 | RON 100 |
| BV2 | RON 5 | RON 5 | RON 5 | BV6 | RON 200 | RON 200 | RON 200 |
| BV3 | RON 10 | RON 10 | RON 10 | BV7 | RON 500 | RON 500 | RON 500 |
| BV3 | RON 50 | RON 50 | RON 50 | BV8 | RON 20 | RON 20 | RON 20 |

_Appendix

L83-RON8(Special Pulse/RS232 A0/RS232 A1)

DIP SWITCHES SETTING: 2(Pulse) DIP SWITCHES SETTING: 2(RS232 A1)

| | FUNCTION | SW1 | SW2 | SW3 | SW4 | |
|---|-------------------|-----|-----|-----|-----|---|
| * | Pulse Normal High | ON | | | | * |
| | Pulse Normal Low | OFF | | | | |
| * | Pulse Mode | | ON | OFF | | |
| | RS232 A0 Mode | | OFF | OFF | | |
| | RS232 A1 Mode | | OFF | ON | | * |
| | Reserved | | ON | ON | | |
| | Reserved | | | | ON | |
| * | Neserved | | | | OFF | * |
| | | | | | | |

| | FUNCTION | SW1 | SW2 | SW3 | SW4 | |
|---|---------------|-----|-----|-----|-----|--|
| * | Reserved | | | | | |
| | | | | | | |
| | Pulse Mode | | ON | OFF | | |
| | RS232 A0 Mode | | OFF | OFF | | |
| * | RS232 A1 Mode | | OFF | ON | | |
| | Reserved | | ON | ON | | |
| | Reserved | | | ON | | |
| * | Reserved | | | | | |

DIP SWITCHES SETTING: 2(RS232 A0)

| | FUNCTION | SW1 | SW2 | SW3 | SW4 |
|---|---------------------------------|-----|-----|-----|-----|
| * | Reserved | | | | |
| | | | | | |
| | Pulse Mode | | ON | OFF | |
| * | RS232 A0 Mode | | OFF | OFF | |
| | RS232 A1 Mode | | OFF | ON | |
| | Reserved | | ON | ON | |
| | Special customer requirements 2 | | | | ON |
| * | Special customer requirements 1 | | | | OFF |

★ Manufacture setting

RS232 A0 INFORMATION Note:Special customer requirements 1

Note:Special customer requirements 2

| BillType Data | | | | | | |
|---------------|--|--|--|--|--|--|
| Denomination | | | | | | |
| RON 1 | | | | | | |
| Reserved | | | | | | |
| Reserved | | | | | | |
| RON 5 | | | | | | |
| RON 10 | | | | | | |
| RON 50 | | | | | | |
| RON 100 | | | | | | |
| RON 200 | | | | | | |
| RON 500 | | | | | | |
| RON 20 | | | | | | |
| | | | | | | |

© 2011 International Currency Technologies Corporation V. 4.0 Part Number : SWI2RO84000-R

[★] Manufacture setting

[★] Manufacture setting