

L83-UAH9

L83 Option Switch Settings : 1(Pulse/RS232 A0/ccNet/ICT104U)

Supported bill HRYVEN 1, 2, 5, 10, 20, 50, 100, 200, 500 9bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★ 1 Pulse / HRYVEN 1 & 5 (Note.3)	OFF	OFF	OFF							
2 Pulses / HRYVEN 1 & 5 (Note.3)	OFF	OFF	ON							
3 Pulses / HRYVEN 1 & 5 (Note.3)	OFF	ON	OFF							
4 Pulses / HRYVEN 1 & 5 (Note.3)	OFF	ON	ON							
5 Pulses / HRYVEN 1 & 5 (Note.3)	ON	OFF	OFF							
10 Pulses / HRYVEN 1 & 5 (Note.3)	ON	OFF	ON							
20 Pulses / HRYVEN 1 & 5 (Note.3)	ON	ON	OFF							
100 Pulses / HRYVEN 1 & 5 (Note.3)	ON	ON	ON							
Fast output Pulse Lo= 50ms Hi=100ms				ON						
★ Slow output Pulse Lo= 50ms Hi=300ms				OFF						
Inhibit level Active Low					ON					
★ Inhibit level Active High					OFF					
★ Accept HRYVEN 1 & 2 (Note.3)						ON				
Reject HRYVEN 1 & 2 (Note.3)						OFF				
★ Accept HRYVEN 5 & 10 & 20 & 50							ON			
Reject HRYVEN 5 & 10 & 20 & 50							OFF			
★ Accept HRYVEN 100 & 200								ON		
Reject HRYVEN 100 & 200								OFF		
★ Accept HRYVEN 500									ON	
Reject HRYVEN 500									OFF	
Simulation BillBox Has Been Removed										ON
★ Default										OFF

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

(3) Pulse Mode:

Dip 6 turn ON ,One Pulse per HRYVEN 1.

Dip 6 turn OFF,One Pulse per HRYVEN 5.

L83-UAH9(Pulse/RS232 A0/ccNet/ICT104U)

DIP SWITCHES SETTING : 2(Pulse)

FUNCTION	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal High	ON			
Credit-Pulse Normal Low	OFF			
RS232 A0 Mode		ON	ON	
★ Pulse Mode		ON	OFF	
ccNet Mode		OFF	OFF	
ICT104U Mode		OFF	ON	
★ Reserved				ON
				OFF

★ Manufacture setting

Currency Assign Data

Interface Bill value	RS232 A0	Pulse		ccNet	ICT104U
		Dip 6 is ON	Dip 6 is OFF		
BV1	1	1	5	1	1
BV2	2	2	10	2	2
BV3	5	5	20	5	5
BV4	10	10	50	10	10
BV5	20	20	100	20	20
BV6	50	50	200	50	50
BV7	100	100	500	100	100
BV8	200	200		200	200
BV9	500	500		500	500

DIP SWITCHES SETTING : 2(RS232 A0)

FUNCTION	SW1	SW2	SW3	SW4
★ Reserved	ON			
	OFF			
★ RS232 A0 Mode		ON	ON	
Pulse Mode		ON	OFF	
ccNet Mode		OFF	OFF	
ICT104U Mode		OFF	ON	
★ Reserved				ON
				OFF

★ Manufacture setting

RS232 A0 INFORMATION

BillType Data	
Code	Denomination
1	HRYPEN 1
2	HRYPEN 2
3	HRYPEN 5
4	HRYPEN 10
5	HRYPEN 20
6	HRYPEN 50
7	HRYPEN 100
8	HRYPEN 200
9	HRYPEN 500

DIP SWITCHES SETTING : 2(ccNet)

FUNCTION	SW1	SW2	SW3	SW4
Baud rate 19200	ON			
★ Baud rate 9600	OFF			
RS232 A0 Mode		ON	ON	
Pulse Mode		ON	OFF	
★ ccNet Mode		OFF	OFF	
ICT104U Mode		OFF	ON	
★ Reserved				ON
				OFF

★ Manufacture setting

DIP SWITCHES SETTING : 2(ICT104U)

FUNCTION	SW1	SW2	SW3	SW4
★ Reserved	ON			
Reserved	OFF			
RS232 A0 Mode		ON	ON	
Pulse Mode		ON	OFF	
ccNet Mode		OFF	OFF	
★ ICT104U Mode		OFF	ON	
★ Reserved				ON
				OFF

★ Manufacture setting