

NE77-SGD3

NE77/P2/P5 DIP SWITCHES SETTING : (Pulse/ICT104U)

Supported bill SGD 2, 5, 10 3bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10	
★	1 Pulse / SGD 1	OFF	OFF									
	2 Pulse / SGD 1	OFF	ON									
	5 Pulse / SGD 1	ON	OFF									
	10 Pulse / SGD 1	ON	ON									
	Fast output Pulse Lo= 50ms Hi=100ms			ON								
★	Slow output Pulse Lo= 50ms Hi=300ms			OFF								
★	Inhibit level Active Low				ON							
	Inhibit level Active High				OFF							
★	Accept SGD 2					ON						
	Reject SGD 2					OFF						
★	Accept SGD 5						ON					
	Reject SGD 5						OFF					
★	Accept SGD 10							ON				
	Reject SGD 10							OFF				
★	Pluse Normal High								ON			
	Pluse Normal Low								OFF			
★	Pulse Mode										ON	
★	ICT104U Mode										OFF	
★	Manufacture Default											ON
	System Default											OFF

(★) Manufacture setting

Note:Dip switches 1 to 4 & 8 are only used for pulse protocol.

Currency Assign Data

Interface Bill value	Pulse	ICT104U
BV1	SGD 2	SGD 2
BV2	SGD 5	SGD 5
BV3	SGD 10	SGD 10