

## V7P-GBP2

### V7P Option Switch Settings: 1(Pulse/ICT104V/ICT104U/MDB)

#### Supported bill

England banknotes : Bank of England £ 5, £ 10

Scotland banknotes: Bank of Scotland £ 5, £ 10

Royal Bank & of Scotland £ 5, £ 10

V7P dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
Reject £ 5	ON											
★ Accept £ 5	OFF											
Reject £ 10		ON										
★ Accept £ 10		OFF										
Reserved			ON									
★ Reserved			OFF									
Reserved				ON								
★ Reserved				OFF								
Reserved					ON							
★ Reserved					OFF							
Reserved						ON						
★ Reserved						OFF						
Harness Disable							ON					
★ Harness Enable							OFF					
Inhibit Active High								ON				
★ Inhibit Active Low								OFF				
★ 1 pulse / £ 5									OFF	OFF		
5 pulses / £ 5									ON	OFF		
10 pulses / £ 5									OFF	ON		
25 pulses / £ 5									ON	ON		
★ Interface Timing Conversion			50ms LO / 50ms HI								OFF	OFF
			60ms LO / 300ms HI								ON	OFF
			30ms LO / 50ms HI								OFF	ON
			150ms LO / 150ms HI								ON	ON

★ Manufacture setting

◆ Note : (1) Default setting.

(2) Use 2nd and 3rd dip of the internal dip-switch to change different interface protocol.

(3) Remove the front cover and the dip-switch in on the CPU board.

## V7P-GBP2(Pulse/ICT104V/ICT104U/MDB)

### Interface Settings: 2(Pulse)

INTERFACE	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
Credit-Pulse Normal LOW	OFF			
★ Pulse Mode		ON	OFF	
ICT104U Mode		OFF	OFF	
ICT104V Mode		OFF	ON	
MDB Mode		ON	ON	
Reserved				ON
★				OFF

★ Manufacture setting

### Interface Settings: 2(ICT104U)

INTERFACE	SW1	SW2	SW3	SW4
★ Reserved	ON			
Reserved	OFF			
Pulse Mode		ON	OFF	
★ ICT104U Mode		OFF	OFF	
ICT104V Mode		OFF	ON	
MDB Mode		ON	ON	
Reserved				ON
★				OFF

★ Manufacture setting

### Currency Assign Data

Interface Bill value	ICT104U	ICT104V	MDB	Pulse
BV1	£ 5	£ 5	£ 5	£ 5
BV2	£ 10	£ 10	£ 10	£ 10

### Interface Settings: 2(ICT104V)

INTERFACE	SW1	SW2	SW3	SW4
★ Reserved	ON			
Reserved	OFF			
Pulse Mode		ON	OFF	
★ ICT104U Mode		OFF	OFF	
ICT104V Mode		OFF	ON	
MDB Mode		ON	ON	
Reserved				ON
★				OFF

★ Manufacture setting

### Interface Settings: 2(MDB)

FUNCTION	SW1	SW2	SW3	SW4
★ Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
Pulse Mode		ON	OFF	
★ ICT104U Mode		OFF	OFF	
ICT104V Mode		OFF	ON	
★ MDB Mode		ON	ON	
Reserved				ON
★				OFF

★ Manufacture setting