

**A7/V7 Option Switch Settings : 1**

Supported bill Ch\$ 1000, 2000, 5000, 10000 4bills.

A7/V7 dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★ Reject Ch\$ 1000	ON											
★ Accept Ch\$ 1000	OFF											
★ Reject Ch\$ 2000		ON										
★ Accept Ch\$ 2000		OFF										
★ Reject Ch\$ 5000			ON									
★ Accept Ch\$ 5000			OFF									
★ Reject Ch\$ 10000				ON								
★ Accept Ch\$ 10000				OFF								
★ Reserved					ON							
★ Reserved					OFF							
★ High Acceptance						ON						
★ High Security							OFF					
★ Harness Disable								ON				
★ Harness Enable								OFF				
★ Inhibit Active High									ON			
★ Inhibit Active Low									OFF			
★ 1 pulse / Ch\$ 1000										OFF	OFF	
2 pulse / Ch\$ 1000										ON	OFF	
4 pulse / Ch\$ 1000										OFF	ON	
20 pulse / Ch\$ 1000										ON	ON	
★ Pulse Speed	50ms on / 50ms off										OFF	OFF
	60ms on / 300ms off										ON	OFF
	30ms on / 50ms off										OFF	ON
	150ms on / 150ms off										ON	ON

◆ Factory configuration has all switches in the OFF position.

Note : (1) Reset the bill acceptor after setting the dip switch.

(2) SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

**A7 Interface Settings: 2**

INTERFACE	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
Credit-Pulse Normal LOW	OFF			
Pulse Mode		ON		
★ RS232 Interface		OFF		
★ Reserved			ON	
			OFF	
				ON
				OFF

**V7 Interface Settings: 3**

INTERFACE	SW1	SW2	SW3	SW4
★ Reserved	ON			
	OFF			
Pulse Mode		ON		
★ MDB Interface		OFF		
★ Reserved			ON	
			OFF	
				ON
				OFF

★ Manufacture setting

