A7/V7 Option Switch Settings: 1 (Pulse/ICT)

Supported bill   S$ 2, 5, 10   3bills.

A7/V7 dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
Reject S$ 2	ON											
★ Accept S$ 2	OFF											
Reject S$ 5		ON										
★ Accept S$ 5		OFF										
Reject S$ 10			ON									
★ Accept S$ 10			OFF									
Reserved				ON								
★ Reserved				OFF								
Reserved					ON							
★ Reserved					OFF							
Reserved						ON						
★ Reserved						OFF						
Harness Disable							ON					
★ Harness Engble							OFF					
Inhiblit Active High								ON				
★ Inhibit Active Low								OFF				
1 pulse / S$ 1									OFF	OFF		
★ 2 pulse / S$ 1									ON	OFF		
4 pulse / S$ 1									OFF	ON		
★ 20 pulse / S$ 1									ON	ON		
★ Pulse Speed — 50ms on / 50ms off											OFF	OFF
Pulse Speed — 60ms on / 300ms off											ON	OFF
Pulse Speed — 30ms on / 50ms off											OFF	ON
★ Pulse Speed — 150ms on / 150ms off											ON	ON

◈ Factory configuration has all switches in the OFF position.

Note : (1) Please reset the bill acceptor after any changes on Dip switch.

(2) SW6 . SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

A7/V7 Interface Settings: 2 (ICT)

INTERFACE	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
Credit-Pulse Normal LOW	OFF			
★ Pulse Mode		ON		
ICT Interface		OFF		
★ Reserved			ON	
Reserved			OFF	
★ Reserved				ON
★ Reserved				OFF

★ Manufacture setting