

V7-KWD4

V7 Option Switch Settings : 1(Pulse/MDB) Supported bill KWD 0.25, 0.5, 1, 5 4bills.

V7 dip-switch settings and functions:

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★	Reject KWD 0.25	ON											
	Accept KWD 0.25	OFF											
★	Reject KWD 0.5		ON										
★	Accept KWD 0.5		OFF										
★	Reject KWD 1			ON									
★	Accept KWD 1			OFF									
★	Reject KWD 5				ON								
★	Accept KWD 5				OFF								
	Reserved				ON								
★	Reserved				OFF								
	Reserved				ON								
★	Reserved				OFF								
	Harness Disable						ON						
★	Harness Enable						OFF						
★	Inhibit Active High							ON					
★	Inhibit Active Low							OFF					
★	1 pulse / KWD 0.25								OFF	OFF			
	2 pulses / KWD 0.25								ON	OFF			
	4 pulses / KWD 0.25								OFF	ON			
	20 pulses / KWD 0.25								ON	ON			
★	Pulse Speed	50ms LO / 50ms HI								OFF	OFF		
		60ms LO / 300ms HI								ON	OFF		
		30ms LO / 50ms HI								OFF	ON		
		150ms LO / 150ms HI								ON	ON		

◆ Factory configuration has all switches in the OFF position.

Note : (1) Reset the bill acceptor after setting the dip switch.

(2) SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

V7-KWD4(Pulse/MDB)

V7 Interface Settings: 2 (Pulse)

	INTERFACE	SW1	SW2	SW3	SW4
★	Credit-Pulse Normal HIGH	ON			
	Credit-Pulse Normal LOW	OFF			
★	Pulse Mode		ON		
	MDB Interface		OFF		
★	Reserved			ON	
				OFF	
					ON
★					OFF

★ Manufacture setting

V7 Interface Settings: 3 (MDB)

	INTERFACE	SW1	SW2	SW3	SW4
★	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
	Scaling Factor (SF) = 1000 Decimal Point Position (DPP) = 3	OFF			
★	Pulse Mode		ON		
	MDB Interface		OFF		
★	Reserved			ON	
				OFF	
					ON
★					OFF

Currency Assign Data

Interface Bill value	Pulse	MDB
BV1	KWD 0.25	KWD 0.25
BV2	KWD 0.5	KWD 0.5
BV3	KWD 1	KWD 1
BV4	KWD 5	KWD 5