

L70-AED5

L70/P5 DIP SWITCHES SETTING : 1(Pulse/ICT104U/MDB)

Supported bill Dh 5, 10, 20, 50, 100

5bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10		
★	1 Pulse / Dh 5	OFF	OFF	OFF									
	2 Pulse / Dh 5	OFF	OFF	ON									
	3 Pulse / Dh 5	OFF	ON	OFF									
	4 Pulse / Dh 5	OFF	ON	ON									
	5 Pulse / Dh 5	ON	OFF	OFF									
	10 Pulse / Dh 5	ON	OFF	ON									
	20 Pulse / Dh 5	ON	ON	OFF									
	100 Pulse / Dh 5	ON	ON	ON									
	Fast output Pulse Lo= 50ms Hi=100ms				ON								
★	Slow output Pulse Lo= 50ms Hi=300ms				OFF								
	Inhibit level Active Low											ON	
★	Inhibit level Active High					OFF							
★	Accept Dh 5					ON							
	Reject Dh 5					OFF							
★	Accept Dh 10											ON	
	Reject Dh 10							OFF					
★	Accept Dh 20											ON	
	Reject Dh 20								OFF				
★	Accept Dh 50												ON
	Reject Dh 50									OFF			
★	Accept Dh 100												
	Reject Dh 100										OFF		

★ Manufacture setting

Note: (1) Please reset the bill acceptor after any changes on Dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

L70-AED5(Pulse/ICT104U/MDB)

DIP SWITCHES SETTING : 2(Pulse)

	FUNCTION	SW1	SW2	SW3	SW4
★	Pulse Normal High	ON			
	Pulse Normal Low	OFF			
★	Pulse Mode		ON	OFF	
	ICT104U Interface		OFF	ON	
	MDB Mode		ON	ON	
	Reserved		OFF	OFF	
★	Reserved				ON
					OFF

★ Manufacture setting

DIP SWITCHES SETTING : 2(ICT104U)

	FUNCTION	SW1	SW2	SW3	SW4
★	Reserved	ON			
		OFF			
	Pulse Mode		ON	OFF	
★	ICT104U Interface		OFF	ON	
	MDB Mode		ON	ON	
	Reserved		OFF	OFF	
★	Reserved				ON
					OFF

★ Manufacture setting

Currency Assign Data

Interface Bill value	ICT104U	Pulse	MDB
BV1	Dh 5	Dh 5	Dh 5
BV2	Dh 10	Dh 10	Dh 10
BV3	Dh 20	Dh 20	Dh 20
BV4	Dh 50	Dh 50	Dh 50
BV5	Dh 100	Dh 100	Dh 100

DIP SWITCHES SETTING : 2(MDB)

	FUNCTION	SW1	SW2	SW3	SW4
★	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
	Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
	Pulse Mode		ON	OFF	
	ICT104U Interface		OFF	ON	
★	MDB Mode		ON	ON	
	Reserved		OFF	OFF	
★	Reserved				ON
					OFF

★ Manufacture setting