

L70-CLP5

L70/P5 DIP SWITCHES SETTING : 1(Pulse/ICT)

Supported bill Ch\$ 1000, 2000, 5000, 10000, 20000 5bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★ 1 Pulse / Ch\$ 1000	OFF	OFF	OFF							
2 Pulse / Ch\$ 1000	OFF	OFF	ON							
3 Pulse / Ch\$ 1000	OFF	ON	OFF							
4 Pulse / Ch\$ 1000	OFF	ON	ON							
5 Pulse / Ch\$ 1000	ON	OFF	OFF							
10 Pulse / Ch\$ 1000	ON	OFF	ON							
20 Pulse / Ch\$ 1000	ON	ON	OFF							
100 Pulse / Ch\$ 1000	ON	ON	ON							
Fast output Pulse Lo= 50ms Hi=100ms				ON						
★ Slow output Pulse Lo= 50ms Hi=300ms				OFF						
Inhibit level Active Low				ON						
★ Inhibit level Active High				OFF						
★ Accept Ch\$ 1000				ON						
Reject Ch\$ 1000				OFF						
★ Accept Ch\$ 2000				ON						
Reject Ch\$ 2000				OFF						
★ Accept Ch\$ 5000				ON						
Reject Ch\$ 5000				OFF						
★ Accept Ch\$ 10000				ON						
Reject Ch\$ 10000				OFF						
★ Accept Ch\$ 20000				ON						
Reject Ch\$ 20000				OFF						

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

L70-CLP5/P5(Pulse/ICT)

DIP SWITCHES SETTING : 2(Pulse)

FUNCTION	SW1	SW2	SW3	SW4
★ Pulse Normal High	ON			
Pulse Normal Low	OFF			
★ Pulse Mode		ON		
ICT104U Interface Mode		OFF		
★ Reserved			ON	
			OFF	
			ON	
			OFF	OFF

★ Manufacture setting

DIP SWITCHES SETTING : 2(ICT)

FUNCTION	SW1	SW2	SW3	SW4
★ Reserved	ON			
Reserved	OFF			
Pulse Mode		ON		
★ ICT104U Interface Mode		OFF		
★ Reserved			ON	
			OFF	
			ON	
			OFF	OFF

★ Manufacture setting

Currency Assign Data

Interface Bill value	ICT104U	Pulse
BV1	Ch\$ 1000	Ch\$ 1000
BV2	Ch\$ 2000	Ch\$ 2000
BV3	Ch\$ 5000	Ch\$ 5000
BV4	Ch\$ 10000	Ch\$ 10000
BV5	Ch\$ 20000	Ch\$ 20000