

L70+/L70F-HNL6

L70+/L70F/P5 DIP SWITCHES SETTING : 1(Pulse/ICT104U)

Supported bill HNL 5, 10, 20, 50, 100, 500 6bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / HNL 5	OFF	OFF	OFF							
	2 Pulses / HNL 5	OFF	OFF	ON							
	3 Pulses / HNL 5	OFF	ON	OFF							
	4 Pulses / HNL 5	OFF	ON	ON							
	5 Pulses / HNL 5	ON	OFF	OFF							
	10 Pulses / HNL 5	ON	OFF	ON							
	20 Pulses / HNL 5	ON	ON	OFF							
	100 Pulses / HNL 5	ON	ON	ON							
	Fast output Pulse Lo= 50ms Hi=100ms				ON						
★	Slow output Pulse Lo= 50ms Hi=300ms				OFF						
	Inhibit level Active Low				ON						
★	Inhibit level Active High				OFF						
★	Accept HNL 5 & 10					ON					
	Reject HNL 5 & 10					OFF					
★	Accept HNL 20						ON				
	Reject HNL 20						OFF				
★	Accept HNL 50							ON			
	Reject HNL 50							OFF			
★	Accept HNL 100								ON		
	Reject HNL 100								OFF		
★	Accept HNL 500									ON	
	Reject HNL 500									OFF	

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

L70+/L70F-HNL6(Pulse/ICT104U)

DIP SWITCHES SETTING : 2(Pulse)

	FUNCTION	SW1	SW2	SW3	SW4
★	Credit - Pulse Normal High	ON			
	Credit - Pulse Normal Low	OFF			
★	Pulse Mode		ON		
	ICT104U Mode		OFF		
★	Reserved			ON	
				OFF	
					ON
★					OFF

Currency Assign Data

Interface	Pulse	ICT104U
Bill value		
BV1	HNL 5	HNL 5
BV2	HNL 10	HNL 10
BV3	HNL 20	HNL 20
BV4	HNL 50	HNL 50
BV5	HNL 100	HNL 100
BV6	Reserved	Reserved
BV7	HNL 500	HNL 500

DIP SWITCHES SETTING : 2(ICT104U)

	FUNCTION	SW1	SW2	SW3	SW4
★	Reserved	ON			
	Reserved	OFF			
	Pulse Mode		ON		
★	ICT104U Mode		OFF		
★	Reserved			ON	
				OFF	
					ON
★					OFF