# L70-ISK2
## L70/P5 DIP SWITCHES SETTING : 1(Pulse/ICT104U)

## Supported bill   ISK   500, 1000   2 bills.

| | FUNCTION | SW1 | SW2 | SW3 | SW4 | SW5 | SW6 | SW7 | SW8 | SW9 | SW10 |
|---|---|---|---|---|---|---|---|---|---|---|---|
| ★ | 1 Pulse / ISK 500 | OFF | OFF | OFF | | | | | | | |
| | 2 Pulse / ISK 500 | OFF | OFF | ON | | | | | | | |
| | 3 Pulse / ISK 500 | OFF | ON | OFF | | | | | | | |
| | 4 Pulse / ISK 500 | OFF | ON | ON | | | | | | | |
| | 5 Pulse / ISK 500 | ON | OFF | OFF | | | | | | | |
| | 10 Pulse / ISK 500 | ON | OFF | ON | | | | | | | |
| | 20 Pulse / ISK 500 | ON | ON | OFF | | | | | | | |
| | 100 Pulse / ISK 500 | ON | ON | ON | | | | | | | |
| | Fast output Pulse Lo= 50ms Hi=100ms | | | | ON | | | | | | |
| ★ | Slow output Pulse Lo= 50ms Hi=300ms | | | | OFF | | | | | | |
| | Inhibit level Active Low | | | | | ON | | | | | |
| ★ | Inhibit level Active High | | | | | OFF | | | | | |
| ★ | Accept  ISK  500 | | | | | | ON | | | | |
| | Reject  ISK   500 | | | | | | OFF | | | | |
| ★ | Accept  ISK  1000 | | | | | | | ON | | | |
| | Reject  ISK  1000 | | | | | | | OFF | | | |
| ★ | Reserved | | | | | | | | ON | | |
| | Reserved | | | | | | | | OFF | | |
| ★ | Reserved | | | | | | | | | ON | |
| | Reserved | | | | | | | | | OFF | |
| ★ | Reserved | | | | | | | | | | ON |
| | Reserved | | | | | | | | | | OFF |

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.
(2) Dip switches 1 to 5 are only used for pulse protocol.

## DIP SWITCHES SETTING : 2

| | FUNCTION | SW1 | SW2 | SW3 | SW4 |
|---|---|---|---|---|---|
| ★ | Credit - Pulse Normal High | ON | | | |
| | Credit - Pulse Normal Low | OFF | | | |
| ★ | Pulse Mode | | ON | | |
| | ICT104U Mode | | OFF | | |
| ★ | Reserved | | | ON | |
| | | | | OFF | |
| | | | | | ON |
| ★ | | | | | OFF |

### Currency Assign Data

| Interface / Bill value | ICT104U | Pulse |
|---|---|---|
| BV1 | 500 | 500 |
| BV2 | 1000 | 1000 |

*Appendix*