

L70-MDL9

L70/P5 DIP SWITCHES SETTING : 1(Pulse/ICT/MDB)

Supported bill MDL 1, 5, 10, 20, 50, 100, 200, 500, 1000 9bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / MDL 1	OFF	OFF	OFF							
	2 Pulse / MDL 1	OFF	OFF	ON							
	3 Pulse / MDL 1	OFF	ON	OFF							
	4 Pulse / MDL 1	OFF	ON	ON							
	5 Pulse / MDL 1	ON	OFF	OFF							
	10 Pulse / MDL 1	ON	OFF	ON							
	20 Pulse / MDL 1	ON	ON	OFF							
	100 Pulse / MDL 1	ON	ON	ON							
	Fast output Pulse Lo= 50ms Hi=100ms				ON						
★	Slow output Pulse Lo= 50ms Hi=300ms				OFF						
	Inhibit level Active Low				ON						
★	Inhibit level Active High				OFF						
★	Accept MDL 1 & 5 & 10				ON						
	Reject MDL 1 & 5 & 10				OFF						
★	Accept MDL 20 & 50				ON						
	Reject MDL 20 & 50				OFF						
★	Accept MDL 100 & 200				ON						
	Reject MDL 100 & 200				OFF						
★	Accept MDL 500				ON						
	Reject MDL 500				OFF						
★	Accept MDL 1000				ON						
	Reject MDL 1000				OFF						

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

L70-MDL9(Pulse/ICT/MDB)

DIP SWITCHES SETTING : 2(Pulse)

	FUNCTION	SW1	SW2	SW3	SW4
★	Pulse Normal High	ON			
	Pulse Normal Low	OFF			
★	Pulse Mode		ON	OFF	
	ICT Interface		OFF	ON	
	MDB Mode		ON	ON	
★	Reserved				ON
					OFF

★ Manufacture setting

Currency Assign Data

Interface Bill value	MDB	Pulse	ICT
BV1	1	1	1
BV2	5	5	5
BV3	10	10	10
BV4	20	20	20
BV5	50	50	50
BV6	100	100	100
BV7	200	200	200
BV8		500	500
BV9		1000	1000

DIP SWITCHES SETTING : 2(ICT)

	FUNCTION	SW1	SW2	SW3	SW4
★	Reserved	ON			
		OFF			
	Pulse Mode		ON	OFF	
★	ICT Interface		OFF	ON	
	MDB Mode		ON	ON	
★	Reserved				ON
					OFF

★ Manufacture setting

DIP SWITCHES SETTING : 2(MDB)

	FUNCTION	SW1	SW2	SW3	SW4
★	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
	Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
	Pulse Mode		ON	OFF	
	ICT Interface		OFF	ON	
★	MDB Mode		ON	ON	
★	Reserved				ON
					OFF

★ Manufacture setting

Note: 500 and 1000 not accept under MDB.