



VND5

L70/P5 DIP SWITCHES SETTING : 1(Special Pulse/MDB)

Supported bill VND 5000, 10000, 20000, 50000,
100000 5bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★ 1 Pulse / VND 5000 (Note.3)	OFF	OFF	OFF							
2 Pulse / VND 5000	OFF	OFF	ON							
3 Pulse / VND 5000	OFF	ON	OFF							
4 Pulse / VND 5000	OFF	ON	ON							
5 Pulse / VND 5000	ON	OFF	OFF							
10 Pulse / VND 5000	ON	OFF	ON							
20 Pulse / VND 5000	ON	ON	OFF							
100 Pulse / VND 5000	ON	ON	ON							
Fast output Pulse Lo= 50ms Hi=100ms				ON						
★ Slow output Pulse Lo= 50ms Hi=300ms				OFF						
Inhibit level Active Low					ON					
★ Inhibit level Active High					OFF					
★ Accept VND 5000 (Note.3)						ON				
Reject VND 5000 (Note.3)						OFF				
★ Accept VND 10000							ON			
Reject VND 10000							OFF			
★ Accept VND 20000								ON		
Reject VND 20000								OFF		
★ Accept VND 50000									ON	
Reject VND 50000									OFF	
★ Accept VND 100000										ON
Reject VND 100000										OFF

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

(3) **Pulse:** When Dip 6 is ON (Accept VND 5000), One Pulse per VND 5000.
When Dip 6 is OFF (Reject VND 5000), One Pulse per VND 10000.

MDB : When Dip 6 is ON (Accept VND 5000)
When Dip 6 is OFF (Reject VND 5000)

L70-VND5/P5(Special Pulse/MDB)

DIP SWITCHES SETTING : 2(Pulse)

FUNCTION	SW1	SW2	SW3	SW4
★ Pulse Normal High	ON			
Pulse Normal Low	OFF			
★ Pulse Mode		ON		
MDB Interface		OFF		
★ Reserved			ON	
			OFF	
				ON
★				OFF

★ Manufacture setting

DIP SWITCHES SETTING : 3(MDB)

FUNCTION	SW1	SW2	SW3	SW4
★ Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
Pulse Mode		ON		
★ MDB Interface		OFF		
★ Reserved			ON	
			OFF	
				ON
★				OFF

★ Manufacture setting