

L70/L70F-ARS5

L70/L70F/P5 DIP SWITCHES SETTING : 1(Pulse/ICT104U/ICT104V/MDB)

Supported bill ARS 50, 100, 200, 500, 1000 5bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★ 1 Pulse / ARS 50	OFF	OFF	OFF							
2 Pulses / ARS 50	OFF	OFF	ON							
3 Pulses / ARS 50	OFF	ON	OFF							
4 Pulses / ARS 50	OFF	ON	ON							
5 Pulses / ARS 50	ON	OFF	OFF							
10 Pulses / ARS 50	ON	OFF	ON							
20 Pulses / ARS 50	ON	ON	OFF							
100 Pulses / ARS 50	ON	ON	ON							
Fast output Pulse Lo= 50ms Hi=100ms				ON						
★ Slow output Pulse Lo= 50ms Hi=300ms				OFF						
Inhibit level Active Low				ON						
★ Inhibit level Active High				OFF						
★ Accept ARS 50				ON						
Reject ARS 50				OFF						
★ Accept ARS 100				ON						
Reject ARS 100				OFF						
★ Accept ARS 200				ON						
Reject ARS 200				OFF						
★ Accept ARS 500				ON						
Reject ARS 500				OFF						
★ Accept ARS 1000				ON						
Reject ARS 1000				OFF						

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

Currency Assign Data

Interface Bill value	Pulse	MDB	ICT104U	ICT104V
BV1	ARS 50	ARS 50	ARS 50	ARS 50
BV2	ARS 100	ARS 100	ARS 100	ARS 100
BV3	ARS 200	ARS 200	ARS 200	ARS 200
BV4	ARS 500	ARS 500	ARS 500	ARS 500

Interface Bill value	Pulse	MDB	ICT104U	ICT104V
BV5	ARS 1000	ARS 1000	ARS 1000	ARS 1000

L70/L70F-ARS5(Pulse/ICT104U/ICT104V/MDB)

DIP SWITCHES SETTING : 2(Pulse)

FUNCTION	SW1	SW2	SW3	SW4
★ Pulse Normal High	ON			
Pulse Normal Low	OFF			
★ Pulse Mode		ON	OFF	
ICT104U Mode		OFF	ON	
MDB Mode		ON	ON	
ICT104V Mode		OFF	OFF	
★ Reserved				ON
				OFF

★ Manufacture setting

DIP SWITCHES SETTING : 2(ICT104U)

FUNCTION	SW1	SW2	SW3	SW4
★ Reserved	ON OFF			
Pulse Mode		ON	OFF	
★ ICT104U Mode		OFF	ON	
MDB Mode		ON	ON	
ICT104V Mode		OFF	OFF	
★ Reserved				ON
				OFF

★ Manufacture setting

DIP SWITCHES SETTING : 2(ICT104V)

FUNCTION	SW1	SW2	SW3	SW4
★ Reserved	ON OFF			
Pulse Mode		ON	OFF	
ICT104U Mode		OFF	ON	
MDB Mode		ON	ON	
★ ICT104V Mode		OFF	OFF	
★ Reserved				ON
				OFF

★ Manufacture setting

DIP SWITCHES SETTING : 2(MDB)

FUNCTION	SW1	SW2	SW3	SW4
★ Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
Pulse Mode		ON	OFF	
ICT104U Mode		OFF	ON	
★ MDB Mode		ON	ON	
ICT104V Mode		OFF	OFF	
★ Reserved				ON
				OFF

★ Manufacture setting