

L70/L70F-CRC5

L70/L70F/P5 DIP SWITCHES SETTING : 1(Pulse/RS232 A0/V2.2)

Supported bill CRC 1000, 2000, 5000, 10000, 20000 5bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10	
★ 1 Pulse / CRC 1000	OFF	OFF	OFF								
2 Pulse / CRC 1000	OFF	OFF	ON								
3 Pulse / CRC 1000	OFF	ON	OFF								
4 Pulse / CRC 1000	OFF	ON	ON								
5 Pulse / CRC 1000	ON	OFF	OFF								
10 Pulse / CRC 1000	ON	OFF	ON								
20 Pulse / CRC 1000	ON	ON	OFF								
100 Pulse / CRC 1000	ON	ON	ON								
Fast output Pulse Lo= 50ms Hi=100ms											ON
★ Slow output Pulse Lo= 50ms Hi=300ms											OFF
Inhibit level Active Low				ON							
★ Inhibit level Active High				OFF							
★ Accept CRC 1000					ON						
Reject CRC 1000					OFF						
★ Accept CRC 2000					ON						
Reject CRC 2000					OFF						
★ Accept CRC 5000					ON						
Reject CRC 5000					OFF						
★ Accept CRC 10000					ON						
Reject CRC 10000					OFF						
★ Accept CRC 20000					ON						
Reject CRC 20000					OFF						

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

Currency Assign Data

Interface Bill value	Pulse	RS232 A0	V2.2
BV1	CRC 1000	CRC 1000	CRC 1000
BV2	CRC 2000	CRC 2000	CRC 2000
BV3	CRC 5000	CRC 5000	CRC 5000
BV4	CRC 10000	CRC 10000	CRC 10000
BV5	CRC 20000	CRC 20000	CRC 20000

L70/L70F-CRC5(Pulse/RS232 A0/V2.2)

DIP SWITCHES SETTING : 2(Pulse)

FUNCTION	SW1	SW2	SW3	SW4
★ Pulse Normal High	ON			
Pulse Normal Low	OFF			
★ Pulse Mode		ON	OFF	
RS232 A0 Mode		ON	ON	
V2.2 Mode		OFF	ON	
Reserved		OFF	OFF	
★ Reserved				ON
				OFF

★ Manufacture setting

DIP SWITCHES SETTING : 2(RS232 A0)

FUNCTION	SW1	SW2	SW3	SW4
★ Reserved	ON			
	OFF			
Pulse Mode		ON	OFF	
★ RS232 A0 Mode		ON	ON	
V2.2 Mode		OFF	ON	
Reserved		OFF	OFF	
★ Reserved				ON
				OFF

BillType Data	
Code	Denomination
1	Reserved
2	Reserved
3	Reserved
4	CRC 1k
5	CRC 2k
6	CRC 5k
7	CRC 10k
8	CRC 20k
9	Reserved

★ Manufacture setting

DIP SWITCHES SETTING : 2(V2.2)

FUNCTION	SW1	SW2	SW3	SW4
★ Reserved	ON			
	OFF			
Pulse Mode		ON	OFF	
RS232 A0 Mode		ON	ON	
★ V2.2 Mode		OFF	ON	
Reserved		OFF	OFF	
★ Reserved				ON
				OFF

★ Manufacture setting