L70+/L70F-HNL5

L70+/L70F DIP SWITCHES SETTING: 1(Pulse/ICT104U)

Supported bill HNL 10, 20, 50, 100, 500 5bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
*	1 Pulse / HNL 10	OFF	OFF	OFF							
	2 Pulse / HNL 10	OFF	OFF	ON							
	3 Pulse / HNL 10	OFF	ON	OFF							
	4 Pulse / HNL 10	OFF	ON	ON							
	5 Pulse / HNL 10	ON	OFF	OFF							
	10 Pulse / HNL 10	ON	OFF	ON							
	20 Pulse / HNL 10	ON	ON	OFF							
	100 Pulse / HNL 10	ON	ON	ON							
	Fast output Pulse Lo= 50ms Hi=100ms				ON						
*	Slow output Pulse Lo= 50ms Hi=300ms				OFF						
	Inhibit level Active Low					ON					
*	Inhibit level Active High					OFF					
*	Accept HNL 10						ON				
	Reject HNL 10						OFF				
*	Accept HNL 20							ON			
	Reject HNL 20							OFF			
*	Accept HNL 50								ON		
	Reject HNL 50								OFF		
*	Accept HNL 100									ON	
	Reject HNL 100									OFF	
*	Accept HNL 500										ON
	Reject HNL 500										OFF

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

_Appendix

L70+/L70F-HNL5(Pulse/ICT104U)

DIP SWITCHES SETTING: 2(Pulse)

	FUNCTION	SW1	SW2	SW3	SW4
*	Pulse Normal High	ON	N		
	Pulse Normal Low	OFF			
*	Pulse Protocol	col ON			
	ICT104U Protocol		OFF		
	Reserved			ON	
*	Reserved	OFF			
	Reserved			ON	
*	Reserved			OFF	

[★] Manufacture setting

DIP SWITCHES SETTING: 2(ICT104U)

	FUNCTION	SW1	SW2	SW3	SW4
*	Reserved				
	Reserved	OFF			
	Pulse Protocol		ON		
*	ICT104U Protocol		OFF		
	Reserved			ON	
*	Reserved	OFF			
	Reserved				ON
*	Reserved			OFF	

[★] Manufacture setting

Currency Assign Data

Interface Bill value	Pulse	ICT104U			
BV1					
BV2	HNL 10	HNL 10			
BV3	HNL 20	HNL 20			
BV4	HNL 50	HNL 50			
BV5	HNL 100	HNL 100			
BV6					
BV7	HNL 500	HNL 500			