

BAM5

P77/P2/P5 DIP SWITCHES SETTING : 1(Pulse/MDB)

Supported bill KM 10, 20, 50, 100, 200 5 bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★ 1 Pulse / KM 10	OFF	OFF	OFF							
2 Pulse / KM 10	OFF	OFF	ON							
3 Pulse / KM 10	OFF	ON	OFF							
4 Pulse / KM 10	OFF	ON	ON							
5 Pulse / KM 10	ON	OFF	OFF							
10 Pulse / KM 10	ON	OFF	ON							
20 Pulse / KM 10	ON	ON	OFF							
100 Pulse / KM 10	ON	ON	ON							
Fast output Pulse Lo= 50ms Hi=100ms				ON						
★ Slow output Pulse Lo= 50ms Hi=300ms				OFF						
Inhibit level Active Low					ON					
★ Inhibit level Active High					OFF					
★ Accept KM 10						ON				
Reject KM 10						OFF				
★ Accept KM 20							ON			
Reject KM 20							OFF			
★ Accept KM 50								ON		
Reject KM 50								OFF		
★ Accept KM 100									ON	
Reject KM 100									OFF	
★ Accept KM 200										ON
Reject KM 200										OFF

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.
(2) Dip switches 1 to 5 are only used for pulse protocol.

P77-BAM5(Pulse/MDB)

DIP SWITCHES SETTING : 2(Pulse)

FUNCTION	SW1	SW2	SW3	SW4
★ Pulse Normal High	ON			
Pulse Normal Low	OFF			
★ Pulse Mode		ON		
MDB Interface		OFF		
Harness Disable			ON	
★ Harness Enable			OFF	
Manufacture Default				ON
★ System Default				OFF

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.
(2) Dip switches 1 & 3 are only used for pulse protocol.

DIP SWITCHES SETTING : 2(MDB)

FUNCTION	SW1	SW2	SW3	SW4
★ Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
Pulse Mode		ON		
★ MDB Interface		OFF		
Reserved			ON	
★			OFF	
Manufacture Default				ON
★ System Default				OFF

★ Manufacture setting

Currency Assign Data

Interface Bill value	MDB	Pulse
BV1	KM 10	KM 10
BV2	KM 20	KM 20
BV3	KM 50	KM 50
BV4	KM 100	KM 100
BV5	KM 200	KM 200