

Supported bill Sw F 10, 20, 50, 100 4bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
*	1 Pulse / Sw F 10	OFF	OFF	OFF							
	2 Pulse / Sw F 10	OFF	OFF	ON							
	3 Pulse / Sw F 10	OFF	ON	OFF							
	4 Pulse / Sw F 10	OFF	ON	ON							
	5 Pulse / Sw F 10	ON	OFF	OFF							
	10 Pulse / Sw F 10	ON	OFF	ON							
	20 Pulse / Sw F 10	ON	ON	OFF							
	100 Pulse / Sw F 10	ON	ON	ON							
	Fast output Pulse Lo= 50ms Hi=100ms				ON						
*	Slow output Pulse Lo= 50ms Hi=300ms				OFF						
	Inhibit level Active Low					ON					
*	Inhibit level Active High					OFF					
*	Accept Sw F 10					•	ON				
	Reject Sw F 10						OFF				
*	Accept Sw F 20							ON			
	Reject Sw F 20							OFF			
*	Accept Sw F 50								ON		
	Reject Sw F 50								OFF		
*	Accept Sw F 100									ON	
	Reject Sw F 100									OFF	
	Reserved										ON
*	Reserved										OFF

<sup>★</sup> Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

## **DIP SWITCHES SETTING: 2**

	FUNCTION	SW1	SW2	SW3	SW4
*	Pulse Normal High	ON			
	Pulse Normal Low	OFF			
*	Pulse Protocol		ON		
	ICT Protocol		OFF		
	Harness Disable			ON	
*	Harness Enable			OFF	
	Manufacture Default				ON
*	System Default				OFF

★ Manufacture setting

<sup>(2)</sup> Dip switches 1 to 5 are only used for pulse protocol.