

P77-RON5

P77/P5 DIP SWITCHES SETTING : 1(Pulse/Parallel A3/MDB)

Supported bill Lei 1, 5, 10, 20, 50 5 bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / Lei 1	OFF	OFF	OFF							
	2 Pulses / Lei 1	OFF	OFF	ON							
	3 Pulses / Lei 1	OFF	ON	OFF							
	4 Pulses / Lei 1	OFF	ON	ON							
	5 Pulses / Lei 1	ON	OFF	OFF							
	10 Pulses / Lei 1	ON	OFF	ON							
	20 Pulses / Lei 1	ON	ON	OFF							
	100 Pulses / Lei 1	ON	ON	ON							
	Fast output Pulse Lo= 50ms Hi=100ms				ON						
★	Slow output Pulse Lo= 50ms Hi=300ms				OFF						
	Inhibit level Active Low				ON						
★	Inhibit level Active High				OFF						
★	Accept Lei 1				ON						
	Reject Lei 1				OFF						
★	Accept Lei 5				ON						
	Reject Lei 5				OFF						
★	Accept Lei 10				ON						
	Reject Lei 10				OFF						
★	Accept Lei 20				ON						
	Reject Lei 20				OFF						
★	Accept Lei 50				ON						
	Reject Lei 50				OFF						

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.
(2) Dip switches 1 to 5 are only used for pulse protocol.

P77-RON5/P5(Pulse/Parallel A3/MDB)

DIP SWITCHES SETTING : 2(Pulse)

	FUNCTION	SW1	SW2	SW3	SW4
★	Credit-Pulse Normal High	ON			
	Credit-Pulse Normal Low	OFF			
★	Pulse Protocol		ON		
	Other Protocol		OFF		
	Harness Disable			ON	
★	Harness Enable			OFF	
	Reserved				ON
★	Reserved				OFF

★ Manufacture setting

DIP SWITCHES SETTING : 3(Parallel A3)

	FUNCTION	SW1	SW2	SW3	SW4
★	Reserved	ON			
		OFF			
	Pulse Protocol		ON		
★	Other Protocol		OFF		
★	Reserved			ON	
				OFF	
★	Parallel A3 Protocol(SW2 OFF)				ON
	MDB Protocol				OFF

★ Manufacture setting

Currency Assign Data

Interface Bill value	Pulse	MDB	Parallel A3
BV1	Lei 1	Lei 1	Lei 1
BV2	Lei 5	Lei 5	Lei 5
BV3	Lei 10	Lei 10	Lei 10
BV4	Lei 50	Lei 50	Lei 50
BV5	Lei 20	Lei 20	

DIP SWITCHES SETTING : 3(MDB)

	FUNCTION	SW1	SW2	SW3	SW4
★	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
	Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
	Pulse Protocol		ON		
★	Other Protocol		OFF		
★	Reserved			ON	
				OFF	
	Parallel A3 Protocol				ON
★	MDB Protocol(SW2 OFF)				OFF

★ Manufacture setting