

P85-BGN5

P85/P5 DIP SWITCHES SETTING : 1(Pulse/ICT)

Supported bill lev 5, 10, 20, 50, 100 5bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★ 1 Pulse / lev 5	OFF	OFF	OFF							
2 Pulse / lev 5	OFF	OFF	ON							
3 Pulse / lev 5	OFF	ON	OFF							
4 Pulse / lev 5	OFF	ON	ON							
5 Pulse / lev 5	ON	OFF	OFF							
10 Pulse / lev 5	ON	OFF	ON							
20 Pulse / lev 5	ON	ON	OFF							
100 Pulse / lev 5	ON	ON	ON							
Fast output Pulse <small>Lo= 50ms Hi=100ms</small>				ON						
★ Slow output Pulse <small>Lo= 50ms Hi=300ms</small>				OFF						
Inhibit level Active Low					ON					
★ Inhibit level Active High					OFF					
★ Accept lev 5						ON				
Reject lev 5						OFF				
★ Accept lev 10							ON			
Reject lev 10							OFF			
★ Accept lev 20								ON		
Reject lev 20								OFF		
★ Accept lev 50									ON	
Reject lev 50									OFF	
★ Accept lev 100										ON
Reject lev 100										OFF

★ Manufacture setting

Note: (1)Please reset the bill acceptor after set the dip switch.

(2)Dip switches 1 to 5 are only used for pulse protocol.

DIP SWITCHES SETTING : 2

FUNCTION	SW1	SW2	SW3	SW4
★ Pulse Normal High	ON			
Pulse Normal Low	OFF			
★ Pulse Protocol		ON		
ICT Protocol		OFF		
Harness Disable			ON	
★ Harness Enable			OFF	
Manufacture Default				ON
★ System Default				OFF

★ Manufacture setting

Currency Assign Data

Bill value	Interface	
	ICT	Pulse
BV1	Lev 5	Lev 5
BV2	Lev 10	Lev 10
BV3	Lev 20	Lev 20
BV4	Lev 50	Lev 50
BV5	Lev 100	Lev 100