

P85-EUR6

P85/P5 DIP SWITCHES SETTING : 1(Pulse/RS232 A0)

Supported bill EUR 5, 10, 20, 50, 100, 200 6bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / EUR 5	OFF	OFF	OFF							
	2 Pulses / EUR 5	OFF	OFF	ON							
	3 Pulses / EUR 5	OFF	ON	OFF							
	4 Pulses / EUR 5	OFF	ON	ON							
	5 Pulses / EUR 5	ON	OFF	OFF							
	10 Pulses / EUR 5	ON	OFF	ON							
	20 Pulses / EUR 5	ON	ON	OFF							
	100 Pulses / EUR 5	ON	ON	ON							
	Fast output Pulse Lo= 50ms Hi=100ms				ON						
★	Slow output Pulse Lo= 50ms Hi=300ms				OFF						
	Inhibit level Active Low					ON					
★	Inhibit level Active High					OFF					
★	Accept EUR 5						ON				
	Reject EUR 5						OFF				
★	Accept EUR 10 & 20							ON			
	Reject EUR 10 & 20							OFF			
★	Accept EUR 50								ON		
	Reject EUR 50								OFF		
★	Accept EUR 100 & 200									ON	
	Reject EUR 100 & 200									OFF	
★	Accept Normal										ON
	Reject EUR 5(2002) & 10(2002)										OFF

★ Manufacture setting

Note: (1)Please reset the bill acceptor after set the dip switch.

(2)Dip switches 1 to 5 are only used for pulse protocol.

Currency Assign Data

Interface Bill value	RS232 A0	Pulse
BV1	EUR 5	EUR 5
BV2	EUR 10	EUR 10
BV3	EUR 20	EUR 20
BV4	EUR 50	EUR 50
BV5	EUR 100	EUR 100
BV6	EUR 200	EUR 200

RS232 A0 INFORMATION

BillType Data	
Code	Denomination
1	Reserved
2	EUR 5
3	EUR 10
4	EUR 20
5	EUR 50
6	EUR 100
7	EUR 200
8	Reserved
9	Reserved

P85-EUR6/P5(Pulse/RS232 A0)

DIP SWITCHES SETTING : 2(Pulse)

	FUNCTION	SW1	SW2	SW3	SW4
★	Credit-Pulse Normal High	ON			
	Credit-Pulse Normal Low	OFF			
★	Pulse Protocol		ON		
	RS232 A0 Protocol		OFF		
	Harness Disable			ON	
★	Harness Enable			OFF	
	Reserved				ON
★	Reserved				OFF

★ Manufacture setting

DIP SWITCHES SETTING : 2(RS232 A0)

	FUNCTION	SW1	SW2	SW3	SW4
★	Reserved	ON			
	Reserved	OFF			
	Pulse Protocol		ON		
★	RS232 A0 Protocol		OFF		
	Reserved			ON	
★	Reserved			OFF	
	Reserved				ON
★	Reserved				OFF

★ Manufacture setting