

TAO-V-MXN5

TAO-V Option Switch Settings: 1(Pulse/MDB)

Supported bill N\$ 20, 50, 100, 200, 500 5bills.

TAO-V dip-switch settings and functions:

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★	Reject N\$ 20	ON											
	Accept N\$ 20	OFF											
★	Reject N\$ 50		ON										
★	Accept N\$ 50		OFF										
★	Reject N\$ 100			ON									
★	Accept N\$ 100			OFF									
★	Reject N\$ 200				ON								
★	Accept N\$ 200				OFF								
★	Reject N\$ 500					ON							
★	Accept N\$ 500					OFF							
★	Reserved					ON							
★	Reserved					OFF							
★	Harness Disable						ON						
★	Harness Enable						OFF						
★	Inhibit Active High							ON					
★	Inhibit Active Low							OFF					
★	1 pulse / N\$ 10								OFF	OFF			
	2 pulse / N\$ 10								ON	OFF			
	5 pulse / N\$ 10								OFF	ON			
	10 pulse / N\$ 10								ON	ON			
★	Interface Timing Conversion	50ms LO / 50ms HI								OFF	OFF		
		60ms LO / 300ms HI								ON	OFF		
		30ms LO / 50ms HI								OFF	ON		
		150ms LO / 150ms HI								ON	ON		

★ Manufacture setting

Note : (1) Default setting

(2) Use 2nd dip switch of the internal dip-switch to change different interface protocol.

TAO-V-MXN5(Pulse/MDB)

Interface Settings: 2(Pulse)

	INTERFACE	SW1	SW2	SW3	SW4
★	Credit-Pulse Normal HIGH	ON			
	Credit-Pulse Normal LOW	OFF			
★	Pulse Mode		ON		
	MDB Interface		OFF		
★	Reserved			ON	
				OFF	
					ON
★					OFF

★ Manufacture setting

Interface Settings: 2(MDB)

	INTERFACE	SW1	SW2	SW3	SW4
★	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	OFF			
★	Pulse Mode		ON		
	MDB Interface		OFF		
★	Reserved			ON	
				OFF	
					ON
★					OFF

★ Manufacture setting

Currency Assign Data

Interface Bill value	Pulse	MDB
BV1	20	20
BV2	50	50
BV3	100	100
BV4	200	200
BV5	500	500