

V7-CZK3

V7 Option Switch Settings : 1(Pulse/MDB)

Supported bill CZK 100, 200, 500 3bills.

V7 dip-switch settings and functions:

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★	Reject CZK 100	ON											
	Accept CZK 100	OFF											
★	Reject CZK 200		ON										
	Accept CZK 200		OFF										
★	Reject CZK 500			ON									
	Accept CZK 500			OFF									
★	Reserved			ON									
	Reserved			OFF									
★	Reserved			ON									
	Reserved			OFF									
★	Reserved				ON								
	Reserved				OFF								
★	Harness disable					ON							
	Harness enable					OFF							
★	Inhibit Active High						ON						
	Inhibit Active Low						OFF						
★	1 pulse / CZK 100							OFF	OFF				
	2 pulses / CZK 100							ON	OFF				
	4 pulses / CZK 100							OFF	ON				
	20 pulses / CZK 100							ON	ON				
★	Pulse Speed	50ms LO / 50ms HI								OFF	OFF		
		60ms LO / 300ms HI								ON	OFF		
		30ms LO / 50ms HI								OFF	ON		
		150ms LO / 150ms HI								ON	ON		

◆ Factory configuration has all switches in the OFF position.

Note : (1) Reset the bill acceptor after setting the dip switch.

(2) SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

(3) SF : Scaling Factor ; DPP : Decimal Point Position.

V7-CZK3(Pulse/MDB)

Interface Settings: 2(Pulse)

	INTERFACE	SW1	SW2	SW3	SW4
★	Credit-Pulse Normal HIGH	ON			
	Credit-Pulse Normal LOW	OFF			
★	Pulse Interface		ON		
	MDB Interface		OFF		
★	Reserved			ON	
				OFF	
★	Reserved				ON
					OFF

★ Manufacture setting

Interface Settings: 2(MDB)

	INTERFACE	SW1	SW2	SW3	SW4
★	Reserved	ON			
	Reserved	OFF			
★	Pulse Interface		ON		
★	MDB Interface (Note)		OFF		
★	Base : 50 SF : 200 DPP : 2 CZK 100 Display : 100.00			OFF	OFF
	Base : 50 SF : 20 DPP : 2 CZK 100 Display : 10.00			ON	OFF
	Base : 50 SF : 20 DPP : 1 CZK 100 Display : 100.0			OFF	ON
	Base : 50 SF : 2 DPP : 0 CZK 100 Display : 100			ON	ON

★ Manufacture setting

Currency Assign Data

Interface Bill value	MDB	Pulse
BV1	CZK 100	CZK 100
BV2	CZK 200	CZK 200
BV3	CZK 500	CZK 500