

V7-MMK4

V7 Option Switch Settings : 1(Pulse/MDB)

Supported bill MMK 100, 200, 500, 1000 4 bills.

V7 dip-switch settings and functions:

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★	Reject MMK 100	ON											
	Accept MMK 100	OFF											
	Reject MMK 200		ON										
★	Accept MMK 200		OFF										
	Reject MMK 500			ON									
★	Accept MMK 500			OFF									
	Reject MMK 1000				ON								
★	Accept MMK 1000				OFF								
	Reserved				ON								
★	Reserved				OFF								
	High Acceptance (Note.2)				ON								
★	High Security				OFF								
	Harness Disable					ON							
★	Harness Enable					OFF							
	Inhibit Active High						ON						
★	Inhibit Active Low						OFF						
★	1 pulse / MMK 100							OFF	OFF				
	2 pulse / MMK 100							ON	OFF				
	5 pulse / MMK 100							OFF	ON				
	20 pulse / MMK 100							ON	ON				
★	Pulse Speed		50ms HI / 50ms LO							OFF	OFF		
			60ms HI / 300ms LO							ON	OFF		
			30ms HI / 50ms LO							OFF	ON		
			150ms HI / 150ms LO							ON	ON		

★ Manufacture setting.

Note.(1.) Please refer to the dip-switch #1 of internal dip-switch for MDB Decimal Point Setup.

(2.) High acceptance mode will increasing accepting rate, however, it will reduce the security level of Bill Acceptor.

V7-MMK4(Pulse/MDB)

V7 Interface Settings: 2 (Pulse)

	INTERFACE	SW1	SW2	SW3	SW4
★	Credit-Pulse Normal HIGH	ON			
	Credit-Pulse Normal LOW	OFF			
★	Pulse Mode		ON		
	MDB Interface (Note.1)		OFF		
	Dummy Coin Changer Disable			ON	
★	Dummy Coin Changer Enable			OFF	
	Reserved				ON
★					OFF

★ Manufacture setting

Interface Settings: 2(MDB)

	INTERFACE	SW1	SW2	SW3	SW4
★	Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	ON			
	Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
	Pulse Mode		ON		
★	MDB Interface (Note.1)		OFF		
	Dummy Coin Changer Disable			ON	
★	Dummy Coin Changer Enable			OFF	
	Reserved				ON
★					OFF

★ Manufacture setting

◆ Factory default setting.

Note : (1) Please refer to the dip-switch #1 of internal dip-switch for MDB Decimal Point Setup.