

# V77E-BGN4

## V77E Option Switch Settings : 1(Pulse/RS232 A0/ccNet/ICT104U)

Supported bill BGN 5, 10, 20, 50 4bills.

V77E dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★ Reject BGN 5	ON											
★ Accept BGN 5	OFF											
★ Reject BGN 10		ON										
★ Accept BGN 10		OFF										
★ Reject BGN 20			ON									
★ Accept BGN 20			OFF									
★ Reject BGN 50				ON								
★ Accept BGN 50				OFF								
★ Reserved					ON							
★ Reserved					OFF							
★ Reserved						ON						
★ Reserved						OFF						
<b>Pulse Mode</b>	<b>Other Mode</b>											
Harness Disable	BA stops working when fishing				ON							
★ Harness Enable	Normal				OFF							
Inhibit Active High								ON				
★ Inhibit Active Low								OFF				
★ 1 pulse / BGN 1								OFF	OFF			
2 pulses / BGN 1								ON	OFF			
4 pulses / BGN 1								OFF	ON			
20 pulses / BGN 1								ON	ON			
★ Pulse Speed	50ms LO / 50ms HI						OFF	OFF				
	60ms LO / 300ms HI						ON	OFF				
	30ms LO / 50ms HI						OFF	ON				
	150ms LO / 150ms HI						ON	ON				

★ Manufacture setting

◆ Factory configuration has all switches in the OFF position.

Note : (1) Default setting.

# V77E-BGN4(Pulse/RS232 A0/ccNet/ICT104U)

## Interface Settings: 2(Pulse)

INTERFACE	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
Credit-Pulse Normal LOW	OFF			
★ Pulse Interface		ON	OFF	
RS232 A0 Interface		OFF	ON	
ccNet Interface		ON	ON	
ICT104U Interface		OFF	OFF	
★ Reserved				ON
				OFF

★ Manufacture setting

## Interface Settings: 2(ccNet)

INTERFACE	SW1	SW2	SW3	SW4
19200 Baud rate	ON			
★ 9600 Baud rate	OFF			
Pulse Interface		ON	OFF	
RS232 A0 Interface		OFF	ON	
★ ccNet Interface		ON	ON	
ICT104U Interface		OFF	OFF	
★ Reserved				ON
				OFF

★ Manufacture setting

## Interface Settings: 2(RS232 A0)

INTERFACE	SW1	SW2	SW3	SW4
Reserved	ON			
★ Reserved	OFF			
Pulse Interface		ON	OFF	
★ RS232 A0 Interface		OFF	ON	
ccNet Interface		ON	ON	
ICT104U Interface		OFF	OFF	
★ Reserved				ON
				OFF

★ Manufacture setting

## RS232 A0 INFORMATION

BillType Data	
Code	Denomination
1	Reserved
2	Reserved
3	BGN 5
4	BGN 10
5	BGN 20
6	BGN 50
7	Reserved
8	Reserved

## Interface Settings: 2(ICT104U)

INTERFACE	SW1	SW2	SW3	SW4
Reserved	ON			
★ Reserved	OFF			
Pulse Interface		ON	OFF	
RS232 A0 Interface		OFF	ON	
ccNet Interface		ON	ON	
★ ICT104U Interface		OFF	OFF	
★ Reserved				ON
				OFF

★ Manufacture setting

## Currency Assign Data

Interface Bill value	Pulse	RS232 A0	ccNet	ICT104U
BV1	BGN 5	BGN 5	BGN 5	BGN 5
BV2	BGN 10	BGN 10	BGN 10	BGN 10
BV3	BGN 20	BGN 20	BGN 20	BGN 20
BV4	BGN 50	BGN 50	BGN 50	BGN 50