

V77E-EUR6

V77E Option Switch Settings : 1(Pulse/Parallel A3/MDB)

Supported bill Euro 5, 10, 20, 50, 100, 200 6bills.

V77E dip-switch settings and functions:

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★	Reject Euro 5	ON											
	Accept Euro 5	OFF											
	Reject Euro 10		ON										
★	Accept Euro 10		OFF										
	Reject Euro 20			ON									
★	Accept Euro 20			OFF									
	Reject Euro 50				ON								
★	Accept Euro 50				OFF								
	Reject Euro 5(2002)&10(2002)				ON								
★	Accept Normal				OFF								
	Reject Euro 100 & 200					ON							
★	Accept Euro 100 & 200					OFF							
	Pulse Mode	Other Mode											
	Harness Disable	BA stops working when fishing						ON					
★	Harness Enable	Normal						OFF					
	Inhibit Active High								ON				
★	Inhibit Active Low								OFF				
★	1 pulse / Euro 5								OFF	OFF			
	5 pulses / Euro 5								ON	OFF			
	10 pulses / Euro 5								OFF	ON			
	20 pulses / Euro 5								ON	ON			
★	Pulse Speed	50ms LO / 50ms HI									OFF	OFF	
		60ms LO / 300ms HI									ON	OFF	
		30ms LO / 50ms HI									OFF	ON	
		150ms LO / 150ms HI									ON	ON	

◆ Factory configuration has all switches in the OFF position.

Note : 1. Default setting.

2. Use both 2nd and 3rd dip of the internal dip-switch to change different interface protocol.

V77E-EUR6(Pulse/Parallel A3/MDB)

Interface Settings: 3(Pulse)

	INTERFACE	SW1	SW2	SW3	SW4
★	Credit-Pulse Normal HIGH	ON			
	Credit-Pulse Normal LOW	OFF			
★	Pulse Interface		ON	OFF	
	Parallel A3 Interface		OFF	ON	
	MDB Interface		ON	ON	
	Reserved		OFF	OFF	
★	Reserved				ON
					OFF

★ Manufacture setting

Currency Assign Data

Interface Bill value	Pulse	Parallel A3	MDB
BV1	Euro 5	Euro 5	Euro 5
BV2	Euro 10	Euro 10	Euro 10
BV3	Euro 20	Euro 20	Euro 20
BV4	Euro 50	Euro 50	Euro 50
BV5	Euro 100		Euro 100
BV6	Euro 200		Euro 200

Interface Settings: 3(Parallel A3)

	INTERFACE	SW1	SW2	SW3	SW4
★	Reserved	ON			
		OFF			
	Pulse Interface		ON	OFF	
★	Parallel A3 Interface		OFF	ON	
	MDB Interface		ON	ON	
	Reserved		OFF	OFF	
★	Reserved				ON
					OFF

★ Manufacture setting

Interface Settings: 3(MDB)

	INTERFACE	SW1	SW2	SW3	SW4
★	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
	Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
	Pulse Interface		ON	OFF	
	Parallel A3 Interface		OFF	ON	
★	MDB Interface		ON	ON	
	Reserved		OFF	OFF	
★	Reserved				ON
					OFF

★ Manufacture setting