

## V77E-GSP2 (GBP2+SCO2)

### V77E Option Switch Settings : 1(Pulse/ICT104U/MDB)

#### Supported bill

English banknotes: England £ 5, £ 10

#### Scottish banknotes:

Royal Bank & Bank of Scotland & Clydesdale Bank £ 5, £ 10

V77E dip-switch settings and functions:

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★	Reject £ 5	ON											
	Accept £ 5	OFF											
★	Reject £ 10		ON										
★	Accept £ 10		OFF										
	Reserved			ON									
★	Reserved			OFF									
	Reserved				ON								
★	Reserved				OFF								
★	Reserved					ON							
★	Reserved					OFF							
	Reserved						ON						
★	Reserved						OFF						
	Harness Disable							ON					
★	Harness Enable							OFF					
	Inhibit Active High								ON				
★	Inhibit Active Low								OFF				
★	1 pulse / £ 5									OFF	OFF		
	5 pulses / £ 5									ON	OFF		
	10 pulses / £ 5									OFF	ON		
	20 pulses / £ 5									ON	ON		
★	Pulse Speed	50ms LO / 50ms HI										OFF	OFF
		60ms LO / 300ms HI										ON	OFF
		30ms LO / 50ms HI										OFF	ON
		150ms LO / 150ms HI										ON	ON

★ Manufacture setting

◆ Factory configuration has all switches in the OFF position.

Note : (1) Reset the bill acceptor after setting the dip switch.

(2) SW6.SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

Use both 2nd and 3rd dip of the internal dip-switch to change different interface protocol.

BV1=5,BV2=10.

## Appendix

## V77E-GSP2 (GBP2+SCO2) (Pulse/ICT104U/MDB)

### Interface Settings: 3(Pulse)

	INTERFACE	SW1	SW2	SW3	SW4
★	Credit-Pulse Normal HIGH	ON			
	Credit-Pulse Normal LOW	OFF			
★	Pulse Interface		ON	OFF	
	ICT104U Interface		OFF	ON	
	MDB Interface		ON	ON	
★	Reserved				ON
					OFF

★ Manufacture setting

### Currency Assign Data

Interface Bill value	ICT104U	Pulse	MDB
BV1	£ 5	£ 5	£ 5
BV2	£ 10	£ 10	£ 10

### Interface Settings: 3(ICT104U)

	INTERFACE	SW1	SW2	SW3	SW4
★	Reserved	ON			
		OFF			
	Pulse Interface		ON	OFF	
★	ICT104U Interface		OFF	ON	
	MDB Interface		ON	ON	
★	Reserved				ON
					OFF

★ Manufacture setting

### Interface Settings: 3(MDB)

	INTERFACE	SW1	SW2	SW3	SW4
★	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
	Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
	Pulse Interface		ON	OFF	
	ICT104U Interface		OFF	ON	
★	MDB Interface		ON	ON	
★	Reserved				ON
					OFF

★ Manufacture setting