

V77E-KGS7

V77E Option Switch Settings : 1(Pulse/RS232 A0/ccNet/ICT104U)

Supported bill KGS 20, 50, 100, 200, 500, 1000, 5000 7bills.

V77E dip-switch settings and functions:

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★	Reject KGS 20 (Note,4)	ON											
★	Accept KGS 20 (Note,4)	OFF											
★	Reject KGS 50 & 100 & 200		ON										
★	Accept KGS 50 & 100 & 200		OFF										
★	Reject KGS 500			ON									
★	Accept KGS 500			OFF									
★	Reject KGS 1000 (old)				ON								
★	Accept KGS 1000 (old)				OFF								
★	Reject KGS 1000 (New)					ON							
★	Accept KGS 1000 (New)					OFF							
★	Reject KGS 5000						ON						
★	Accept KGS 5000						OFF						
★	Harness Disable							ON					
★	Harness Enable							OFF					
★	Inhibit Active High								ON				
★	Inhibit Active Low								OFF				
★	1 pulse / KGS 10 & 50								OFF	OFF			
★	5 pulses / KGS 10 & 50								ON	OFF			
★	10 pulses / KGS 10 & 50								OFF	ON			
★	20 pulses / KGS 10 & 50								ON	ON			
★	Pulse Speed	50ms LO / 50ms HI									OFF	OFF	
		60ms LO / 300ms HI									ON	OFF	
		30ms LO / 50ms HI									OFF	ON	
		150ms LO / 150ms HI									ON	ON	

★ Manufacture setting

◆ Factory configuration has all switches in the OFF position.

Note : (1) Default setting.

(2) SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

(3) Use 2nd and 3rd dip of the internal dip-switch to change different interface protocol.

(4) Pulse Mode : When Dip 1 is OFF, One Pulse per KGS 10.
When Dip 1 is ON, One Pulse per KGS 50.

V77E-KGS7(Pulse/RS232 A0/ccNet/ICT104U)

Interface Settings: 2(Pulse)

	INTERFACE	SW1	SW2	SW3	SW4
★	Credit-Pulse Normal HIGH	ON			
	Credit-Pulse Normal LOW	OFF			
★	Pulse Interface		ON	OFF	
	RS232 A0 Interface		OFF	ON	
	ccNet Interface		ON	ON	
	ICT104U Interface		OFF	OFF	
★	Reserved				ON
					OFF

★ Manufacture setting

Interface Settings: 2(ccNet)

	INTERFACE	SW1	SW2	SW3	SW4
	19200 Baud rate	ON			
★	9600 Baud rate	OFF			
	Pulse Interface		ON	OFF	
	RS232 A0 Interface		OFF	ON	
★	ccNet Interface		ON	ON	
	ICT104U Interface		OFF	OFF	
★	Reserved				ON
					OFF

★ Manufacture setting

Interface Settings: 2(RS232 A0)

	INTERFACE	SW1	SW2	SW3	SW4
	Reserved	ON			
★	Reserved	OFF			
	Pulse Interface		ON	OFF	
★	RS232 A0 Interface		OFF	ON	
	ccNet Interface		ON	ON	
	ICT104U Interface		OFF	OFF	
★	Reserved				ON
					OFF

★ Manufacture setting

RS232 A0 INFORMATION

BillType Data	
Code	Denomination
1	Reserved
2	Reserved
3	KGS 20
4	KGS 50
5	KGS 100
6	KGS 200
7	KGS 500
8	KGS 1000
9	KGS 5000

Interface Settings: 2(ICT104U)

	INTERFACE	SW1	SW2	SW3	SW4
	Reserved	ON			
★	Reserved	OFF			
	Pulse Interface		ON	OFF	
	RS232 A0 Interface		OFF	ON	
	ccNet Interface		ON	ON	
★	ICT104U Interface		OFF	OFF	
★	Reserved				ON
					OFF

★ Manufacture setting

Currency Assign Data

Interface Bill value	Pulse		RS232 A0	ccNet	ICT104U
	Dip 1 OFF	Dip 1 ON			
BV1	20		20	20	20
BV2	50	50	50	50	50
BV3	100	100	100	100	100
BV4	200	200	200	200	200
BV5	500	500	500	500	500
BV6	1000 (Old)	1000 (Old)	1000	1000 (Old)	1000
BV7	1000 (New)	1000 (New)	5000	1000 (New)	5000
BV8	5000	5000		5000	