

V77E-KZT5

V77E Option Switch Settings : 1(Pulse/MDB/RS232 B0)

Supported bill KZT 200, 500, 1000, 2000, 5000 5bills.

V77E dip-switch settings and functions:

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★	Reject KZT 200	ON											
	Accept KZT 200	OFF											
	Reject KZT 500		ON										
★	Accept KZT 500		OFF										
	Reject KZT 1000			ON									
★	Accept KZT 1000			OFF									
	Reject KZT 2000				ON								
★	Accept KZT 2000				OFF								
	Reject KZT 5000				ON								
★	Accept KZT 5000				OFF								
	Reserved				ON								
★	Reserved				OFF								
	Harness Disable					ON							
★	Harness Enable					OFF							
	Inhibit Active High						ON						
★	Inhibit Active Low						OFF						
★	1 pulse / KZT 100							OFF		OFF			
	2 pulse / KZT 100							ON		OFF			
	5 pulse / KZT 100							OFF		ON			
	20 pulse / KZT 100							ON		ON			
★	Pulse Speed	50ms on / 50ms off								OFF		OFF	
		60ms on / 300ms off								ON		OFF	
		30ms on / 50ms off								OFF		ON	
		150ms on / 150ms off								ON		ON	

★ Manufacture setting

◆ Factory configuration has all switches in the OFF position.

Note : (1) Reset the bill acceptor after setting the dip switch.

(2) SW6.SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

V77E-KZT5(Pulse/MDB/RS232 B0)

Interface Settings: 2(Pulse)

	INTERFACE	SW1	SW2	SW3	SW4
★	Credit-Pulse Normal HIGH	ON			
	Credit-Pulse Normal LOW	OFF			
★	Pulse Interface		ON	OFF	
	MDB Interface		ON	ON	
	RS232 B0 Interface		OFF	ON	
★	Reserved				ON
					OFF

★ Manufacture setting

Interface Settings: 2(MDB)

	INTERFACE	SW1	SW2	SW3	SW4
★	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
	Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
	Pulse Interface		ON	OFF	
★	MDB Interface		ON	ON	
	RS232 B0 Interface		OFF	ON	
★	Reserved				ON
					OFF

★ Manufacture setting

Interface Settings: 2(RS232 B0)

	INTERFACE	SW1	SW2	SW3	SW4
	Baud rate 19200	ON			
★	Baud rate 9600	OFF			
	Pulse Interface		ON	OFF	
	MDB Interface		ON	ON	
★	RS232 B0 Interface		OFF	ON	
★	Reserved				ON
					OFF

★ Manufacture setting

Currency Assign Data

Interface Bill value	Pulse	MDB	RS232 B0
BV1	200	200	200
BV2	500	500	500
BV3	1,000	1,000	1,000
BV4	2,000	2,000	2,000
BV5	5,000	5,000	5,000