

V7E/LX7-COP7

V7E/LX7 Option Switch Settings: 1(Pulse/RS232 A0/V2.2)

Supported bill Col\$ 1000, 2000, 5000, 10000, 20000, 50000, 100000
7bills.

V7E/LX7 dip-switch settings and functions:

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★	Reject Col\$ 1000 & 2000	ON											
★	Accept Col\$ 1000 & 2000	OFF											
	Reject Col\$ 5000		ON										
★	Accept Col\$ 5000		OFF										
	Reject Col\$ 10000			ON									
★	Accept Col\$ 10000			OFF									
	Reject Col\$ 20000				ON								
★	Accept Col\$ 20000				OFF								
	Reject Col\$ 50000 & 100000					ON							
★	Accept Col\$ 50000 & 100000					OFF							
	Reserved						ON						
★	Reserved						OFF						
	Harness Disable							ON					
★	Harness Enable							OFF					
	Inhibit Active High								ON				
★	Inhibit Active Low								OFF				
★	1 pulse / Col\$ 1000								OFF	OFF			
	2 pulse / Col\$ 1000								ON	OFF			
	4 pulse / Col\$ 1000								OFF	ON			
	20 pulse / Col\$ 1000								ON	ON			
★	Pulse Speed	50ms LO / 50ms HI									OFF	OFF	
		60ms LO / 300ms HI									ON	OFF	
		30ms LO / 50ms HI									OFF	ON	
		150ms LO / 150ms HI									ON	ON	

★ Manufacture setting

◆ Note : (1) Default setting

V7E/LX7-COP7(Pulse/RS232 A0/V2.2)

DIP SWITCHES SETTING : 2(Pulse)

	FUNCTION	SW1	SW2	SW3	SW4
★	Pulse Normal High	ON			
	Pulse Normal Low	OFF			
★	Pulse Mode		ON	OFF	
	RS232 A0 Mode		OFF	ON	
	V2.2 Mode		ON	ON	
	Reserved		OFF	OFF	
★	Reserved				ON
					OFF

★ Manufacture setting

DIP SWITCHES SETTING : 2(RS232 A0)

	FUNCTION	SW1	SW2	SW3	SW4
★	Reserved	ON			
		OFF			
	Pulse Mode		ON	OFF	
★	RS232 A0 Mode		OFF	ON	
	V2.2 Mode		ON	ON	
	Reserved		OFF	OFF	
★	Reserved				ON
					OFF

RS232 A0 INFORMATION

BillType Data	
Code	Denomination
1	Col\$ 1000
2	Col\$ 2000
3	Col\$ 5000
4	Col\$ 10000
5	Col\$ 20000
6	Col\$ 50000
7	Col\$ 100000
8	Reserved
9	Reserved

★ Manufacture setting

DIP SWITCHES SETTING : 2(V2.2)

	FUNCTION	SW1	SW2	SW3	SW4
★	Reserved	ON			
		OFF			
	Pulse Mode		ON	OFF	
	RS232 A0 Mode		OFF	ON	
★	V2.2 Mode		ON	ON	
	Reserved		OFF	OFF	
★	Reserved				ON
					OFF

★ Manufacture setting

Currency Assign Data

Interface Bill value	Pulse	RS232 A0	V2.2
BV1	Col\$ 1000	Col\$ 1000	Col\$ 1000
BV2	Col\$ 2000	Col\$ 2000	Col\$ 2000
BV3	Col\$ 5000	Col\$ 5000	Col\$ 5000
BV4	Col\$ 10000	Col\$ 10000	Col\$ 10000
BV5	Col\$ 20000	Col\$ 20000	Col\$ 20000
BV6	Col\$ 50000	Col\$ 50000	Col\$ 50000
BV7	Col\$ 100000	Col\$ 100000	Col\$ 100000