

V7E-KRW4

V7E Option Switch Settings: 1(Pulse/ICT/MDB/ICT for VCCS)

Supported bill ₩ 1000, 5000, 10000, 50000 4bills.

V7E dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★ Reject ₩ 1000	ON											
★ Accept ₩ 1000	OFF											
★ Reject ₩ 5000		ON										
★ Accept ₩ 5000		OFF										
★ Reject ₩ 10000			ON									
★ Accept ₩ 10000			OFF									
★ Reject ₩ 50000				ON								
★ Accept ₩ 50000				OFF								
★ Reserved				ON								
★ Reserved				OFF								
★ Reserved				ON								
★ Reserved				OFF								
★ Harness Disable							ON					
★ Harness Enable							OFF					
★ Inhibit Active High							ON					
★ Inhibit Active Low							OFF					
★ 1 pulse / ₩ 1000								OFF	OFF			
5 pulses / ₩ 1000								ON	OFF			
10 pulses / ₩ 1000								OFF	ON			
20 pulses / ₩ 1000								ON	ON			
★ Interface Timing Conversion		50ms on / 50ms off								OFF	OFF	
		60ms on / 300ms off								ON	OFF	
		30ms on / 50ms off								OFF	ON	
		150ms on / 150ms off								ON	ON	

★ Manufacture setting

◆ Note : (1) Please reset the bill acceptor after any changes on Dip switch.

(2) SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

V7E-KRW4

Interface Settings: 2(Pulse)

INTERFACE	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
Credit-Pulse Normal LOW	OFF			
★ Pulse Mode		ON	OFF	
ICT Mode		OFF	OFF	
ICT for VCCS		OFF	ON	
MDB Interface		ON	ON	
★ Reserved				ON
				OFF

★ Manufacture setting

Interface Settings: 2(ICT/ICT for VCCS)

INTERFACE	SW1	SW2	SW3	SW4
★ Not Used	ON			
Not Used	OFF			
Pulse Mode		ON	OFF	
★ ICT Mode		OFF	OFF	
ICT for VCCS		OFF	ON	
MDB Interface		ON	ON	
★ Reserved				ON
				OFF

INTERFACE	SW1	SW2	SW3	SW4
★ Not Used	ON			
Not Used	OFF			
Pulse Mode		ON	OFF	
★ ICT Mode		OFF	OFF	
ICT for VCCS		OFF	ON	
MDB Interface		ON	ON	
★ Reserved				ON
				OFF

★ Manufacture setting

★ Manufacture setting

Interface Settings: 2(MDB)

FUNCTION	SW1	SW2	SW3	SW4
★ Scaling Factor (SF) = 10 Decimal Point Position (DPP) = 1	ON			
Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
Pulse Mode		ON	OFF	
ICT Mode		OFF	OFF	
ICT for VCCS		OFF	ON	
★ MDB Interface		ON	ON	
★ Reserved				ON
				OFF

★ Manufacture setting

Currency Assign Data

Interface Bill value	Pulse	ICT	MDB
BV1	1000	1000	1000
BV2	5000	5000	5000
BV3	10000	10000	10000
BV4	50000	50000	50000