

L70T-AUD5

L70T DIP SWITCHES SETTING : 1(Pulse/RS232 A0/V2.2)

Supported bill AUD 5, 10, 20, 50, 100 5bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★ 1 Pulse / AUD 5	OFF	OFF	OFF							
2 Pulses / AUD 5	OFF	OFF	ON							
3 Pulses / AUD 5	OFF	ON	OFF							
4 Pulses / AUD 5	OFF	ON	ON							
5 Pulses / AUD 5	ON	OFF	OFF							
10 Pulses / AUD 5	ON	OFF	ON							
20 Pulses / AUD 5	ON	ON	OFF							
100 Pulses / AUD 5	ON	ON	ON							
Fast output Pulse Lo= 50ms Hi=100ms				ON						
★ Slow output Pulse Lo= 50ms Hi=300ms				OFF						
Inhibit level Active Low					ON					
★ Inhibit level Active High					OFF					
★ Accept AUD 5						ON				
Reject AUD 5						OFF				
★ Accept AUD 10							ON			
Reject AUD 10							OFF			
★ Accept AUD 20								ON		
Reject AUD 20								OFF		
★ Accept AUD 50									ON	
Reject AUD 50									OFF	
★ Accept AUD 100										ON
Reject AUD 100										OFF

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

Currency Assign Data

Interface Bill value	Pulse	RS232 A0	V2.2
BV1	5	5	5
BV2	10	10	10
BV3	20	20	20
BV4	50	50	50
BV5	100	100	100

L70T-AUD5(Pulse/RS232 A0/V2.2)

DIP SWITCHES SETTING : 2(Pulse)

FUNCTION	SW1	SW2	SW3	SW4
★ Pulse Normal High	ON			
Pulse Normal Low	OFF			
★ Pulse Mode		ON	OFF	
RS232 A0 Mode		ON	ON	
V2.2 Mode		OFF	ON	
Reserved		OFF	OFF	
Reserved				ON
★ Reserved				OFF

★ Manufacture setting

DIP SWITCHES SETTING : 2(RS232 A0)

FUNCTION	SW1	SW2	SW3	SW4
★ Reserved	ON			
Reserved	OFF			
Pulse Mode		ON	OFF	
★ RS232 A0 Mode		ON	ON	
V2.2 Mode		OFF	ON	
Reserved		OFF	OFF	
Reserved				ON
★ Reserved				OFF

RS232 A0 INFORMATION

BillType Data	
Code	Denomination
1	Reserved
2	Reserved
3	AUD 5
4	AUD 10
5	AUD 20
6	AUD 50
7	AUD 100
8	Reserved

★ Manufacture setting

DIP SWITCHES SETTING : 2(V2.2)

FUNCTION	SW1	SW2	SW3	SW4
★ Reserved	ON			
Reserved	OFF			
Pulse Mode		ON	OFF	
RS232 A0 Mode		ON	ON	
★ V2.2 Mode		OFF	ON	
Reserved		OFF	OFF	
Reserved				ON
★ Reserved				OFF

★ Manufacture setting