

THB5

L77&L77F/P5 DIP SWITCHES SETTING : 1(Pulse/RS232 A0)

Supported bill THB 20, 50, 100, 500, 1000 5bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★ 1 Pulse / THB 10	OFF	OFF	OFF							
2 Pulse / THB 10	OFF	OFF	ON							
3 Pulse / THB 10	OFF	ON	OFF							
4 Pulse / THB 10	OFF	ON	ON							
5 Pulse / THB 10	ON	OFF	OFF							
10 Pulse / THB 10	ON	OFF	ON							
20 Pulse / THB 10	ON	ON	OFF							
100 Pulse / THB 10	ON	ON	ON							
Fast output Pulse Lo= 50ms Hi=100ms				ON						
★ Slow output Pulse Lo= 50ms Hi=300ms				OFF						
Inhibit level Active Low					ON					
★ Inhibit level Active High					OFF					
★ Accept THB 20						ON				
Reject THB 20						OFF				
★ Accept THB 50							ON			
Reject THB 50							OFF			
★ Accept THB 100								ON		
Reject THB 100								OFF		
★ Accept THB 500									ON	
Reject THB 500									OFF	
★ Accept THB 1000										ON
Reject THB 1000										OFF

★ Manufacture setting

Note: (1) Please reset the bill acceptor after any changes on Dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

L77&L77F-THB5(Pulse/RS232 A0)

DIP SWITCHES SETTING : 2(Pulse)

FUNCTION	SW1	SW2	SW3	SW4
★ Pulse Normal High	ON			
Pulse Normal Low	OFF			
★ Pulse Mode		ON		
RS232 A0 Interface Mode		OFF		
★ Reserved			ON	
			OFF	
				ON
				OFF

★ Manufacture setting

DIP SWITCHES SETTING : 2(RS232 A0)

FUNCTION	SW1	SW2	SW3	SW4
★ Reserved	ON			
	OFF			
Pulse Mode		ON		
★ RS232 A0 Interface Mode		OFF		
★ Reserved			ON	
			OFF	
				ON
				OFF

★ Manufacture setting

ESCROW DATA	
Code	Denomination
61h	Reserved
62h	THA 20
63h	THA 50
64h	THA 100
65h	Reserved
66h	THA 500
67h	THA 1000
68h	Reserved
69h	Reserved

CURRENCY ASSIGN DATA			
Code	Country	Denomination	Exp.
61h	00h	00h	00h
62h	12h	02h	01h
63h	12h	05h	01h
64h	12h	0Ah	01h
65h	00h	00h	00h
66h	12h	32h	01h
67h	12h	64h	01h
68h	00h	00h	00h
69h	00h	00h	00h

Currency Assign Data

Interface Bill value	Pulse	RS232 A0
BV1	THB 20	THB 20
BV2	THB 50	THB 50
BV3	THB 100	THB 100
BV4	THB 500	THB 500
BV5	THB 1000	THB 1000