

KZT5

L77&L77F-P3/P6 DIP SWITCHES SETTING : 1(Pulse/ICT)

Supported bill T 200, 500, 1000, 2000, 5000 5bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / T 100	OFF	OFF	OFF							
	2 Pulse / T 100	OFF	OFF	ON							
	3 Pulse / T 100	OFF	ON	OFF							
	4 Pulse / T 100	OFF	ON	ON							
	5 Pulse / T 100	ON	OFF	OFF							
	10 Pulse / T 100	ON	OFF	ON							
	20 Pulse / T 100	ON	ON	OFF							
	100 Pulse / T 100	ON	ON	ON							
	Fast output Pulse Lo= 50ms Hi=100ms				ON						
★	Slow output Pulse Lo= 50ms Hi=300ms				OFF						
	Inhibit level Active Low				ON						
★	Inhibit level Active High				OFF						
★	Accept T 200					ON					
	Reject T 200					OFF					
★	Accept T 500						ON				
	Reject T 500						OFF				
★	Accept T 1000							ON			
	Reject T 1000							OFF			
★	Accept T 2000								ON		
	Reject T 2000								OFF		
★	Accept T 5000									ON	
	Reject T 5000									OFF	

★ Manufacture setting

Note:(1)Please reset the bill acceptor after set the dip switch.

(2)Dip switches 1 to 5 are only used for pulse protocol.

DIP SWITCHES SETTING : 2

	FUNCTION	SW1	SW2	SW3	SW4
★	Pulse Normal High	ON			
	Pulse Normal Low	OFF			
★	Pulse Mode		ON		
	ICT Protocol Mode		OFF		
	Reserved			ON	
★	Reserved			OFF	
	Reserved				ON
★	Reserved				OFF

★ Manufacture setting

Currency Assign Data

Interface Bill value	Pulse	ICT
BV1	200	200
BV2	500	500
BV3	1000	1000
BV4	2000	2000
BV5	5000	5000