

# HRK5

## L77&L77F-P3/P6 DIP SWITCHES SETTING : 1(Pulse/ICT)

Supported bill kn 10, 20, 50, 100, 200 5bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★ 1 Pulse / kn 10	OFF	OFF	OFF							
2 Pulse / kn 10	OFF	OFF	ON							
3 Pulse / kn 10	OFF	ON	OFF							
4 Pulse / kn 10	OFF	ON	ON							
5 Pulse / kn 10	ON	OFF	OFF							
10 Pulse / kn 10	ON	OFF	ON							
20 Pulse / kn 10	ON	ON	OFF							
100 Pulse / kn 10	ON	ON	ON							
Fast output Pulse <small>Lo= 50ms Hi=100ms</small>				ON						
★ Slow output Pulse <small>Lo= 50ms Hi=300ms</small>				OFF						
Inhibit level Active Low					ON					
★ Inhibit level Active High					OFF					
★ Accept kn 10						ON				
Reject kn 10						OFF				
★ Accept kn 20							ON			
Reject kn 20							OFF			
★ Accept kn 50								ON		
Reject kn 50								OFF		
★ Accept kn 100									ON	
Reject kn 100									OFF	
★ Accept kn 200										ON
Reject kn 200										OFF

## DIP SWITCHES SETTING : 2

FUNCTION	SW1	SW2	SW3	SW4	
★ Pulse Normal High	ON				
Pulse Normal Low	OFF				
★ Pulse Mode					ON
ICT Protocol Mode					OFF
★ Reserved			ON		
			OFF		
				ON	
				OFF	

### Currency Assign Data

Interface Bill value	Pulse	ICT
BV1	10	10
BV2	20	20
BV3	50	50
BV4	100	100
BV5	200	200

★ Manufacture setting

Note:(1)Please reset the bill acceptor after set the dip switch.

(2)Dip switches 1 to 5 are only used for pulse protocol.