

# PL77&L77F-HKD4

## PL77-P3/P6 DIP SWITCHES SETTING : 1(Pulse/ICT104U/ICT104V/MDB) L77F-P2/P5

Supported bill HKD 10, 20, 50, 100 4bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★ 1 Pulse / HKD 10	OFF	OFF	OFF							
2 Pulse / HKD 10	OFF	OFF	ON							
3 Pulse / HKD 10	OFF	ON	OFF							
4 Pulse / HKD 10	OFF	ON	ON							
5 Pulse / HKD 10	ON	OFF	OFF							
10 Pulse / HKD 10	ON	OFF	ON							
20 Pulse / HKD 10	ON	ON	OFF							
100 Pulse / HKD 10	ON	ON	ON							
Fast output Pulse Lo= 50ms Hi=100ms				ON						
★ Slow output Pulse Lo= 50ms Hi=300ms				OFF						
Inhibit level Active Low					ON					
★ Inhibit level Active High					OFF					
★ Accept HKD 10						ON				
Reject HKD 10						OFF				
★ Accept HKD 20							ON			
Reject HKD 20							OFF			
★ Accept HKD 50								ON		
Reject HKD 50								OFF		
★ Accept HKD 100									ON	
Reject HKD 100									OFF	
★ Reserved										ON
Reserved										OFF

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

# PL77-HKD4 P3/P6 (Pulse/ICT104U/ICT104V/MDB) L77F-HKD4 P2/P5

## DIP SWITCHES SETTING : 2(Pulse)

FUNCTION	SW1	SW2	SW3	SW4
★ Pulse Normal High	ON			
Pulse Normal Low	OFF			
★ Pulse Mode		ON	OFF	
ICT104U Mode		OFF	ON	
MDB Mode		ON	ON	
ICT104V Mode		OFF	OFF	
Reserved				ON
★				OFF

★ Manufacture setting

## Currency Assign Data

Interface Bill value	ICT104U	ICT104V	Pulse	MDB
BV1	KHD 10	KHD 10	KHD 10	KHD 10
BV2	KHD 20	KHD 20	KHD 20	KHD 20
BV3	KHD 50	KHD 50	KHD 50	KHD 50
BV4	KHD 100	KHD 100	KHD 100	KHD 100

## DIP SWITCHES SETTING : 2(ICT104U)

FUNCTION	SW1	SW2	SW3	SW4
★ Reserved	ON			
	OFF			
Pulse Mode		ON	OFF	
★ ICT104U Mode		OFF	ON	
MDB Mode		ON	ON	
ICT104V Mode		OFF	OFF	
Reserved				ON
★				OFF

★ Manufacture setting

## DIP SWITCHES SETTING : 2(ICT104V)

FUNCTION	SW1	SW2	SW3	SW4
★ Reserved	ON			
	OFF			
Pulse Mode		ON	OFF	
★ ICT104U Mode		OFF	ON	
MDB Mode		ON	ON	
★ ICT104V Mode		OFF	OFF	
Reserved				ON
★				OFF

★ Manufacture setting

## DIP SWITCHES SETTING : 2(MDB)

FUNCTION	SW1	SW2	SW3	SW4
★ Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
Pulse Mode		ON	OFF	
★ ICT104U Mode		OFF	ON	
MDB Mode		ON	ON	
ICT104V Mode		OFF	OFF	
Reserved				ON
★				OFF

★ Manufacture setting