

**A7/V7-TWD4**

**A7/V7 Option Switch Settings**

Supported bill TWD 100, 200, 500, 1000 4bills.

A7/V7 dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
Reject TWD 100	ON											
Accept TWD 100	OFF											
Reject TWD 200		ON										
Accept TWD 200		OFF										
Reject TWD 500			ON									
Accept TWD 500			OFF									
Reject TWD 1000				ON								
Accept TWD 1000				OFF								
Reserved					ON							
Reserved					OFF							
High Acceptance						ON						
High Security						OFF						
Harness Disable							ON					
Harness Enable							OFF					
Inhibit Active High								ON				
Inhibit Active Low								OFF				
1 pulse / 100 dollar									OFF	OFF		
2 pulse / 100 dollar									ON	OFF		
4 pulse / 100 dollar									OFF	ON		
20 pulse / 100 dollar									ON	ON		
Pulse Speed	50ms on / 50ms off								OFF	OFF		
	60ms on / 300ms off								ON	OFF		
	30ms on / 50ms off								OFF	ON		
	150ms on / 150ms off								ON	ON		

◆ Factory configuration has all switches in the OFF position.

Note : (1) Reset the bill acceptor after setting the dip switch.

(2) SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

**A7/V7-TWD4**

**A7 Interface Settings: 2**

INTERFACE	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
Credit-Pulse Normal LOW	OFF			
Pulse Mode		ON		
★ RS232 Interface		OFF		
Reserved			ON	
			OFF	
				ON
				OFF

**V7 Interface Settings: 3**

INTERFACE	SW1	SW2	SW3	SW4
Reserved	ON			
	OFF			
Pulse Mode		ON		
★ MDB Interface		OFF		
Reserved			ON	
			OFF	
				ON
				OFF

★ Manufacture setting

◆ Note: Refer to "SW1" setting.