

# UCH

---

## UCH Series Coin Hopper

- Wide range of coin size acceptable in single hardware
- High payout speed
- Payout to last coin
- Convenient firmware upgrade via USB flash drive
- Twin connection coin path
- Anti-jamming design
- Power supply for both 12V and 24V
- Easy installation base
- Easy maintenance



The ICT logo is located in the bottom left corner. It consists of the letters 'ICT' in a bold, blue, sans-serif font, with a red dot above the 'I'. The logo is set against a blue background with a pattern of white circles and lines.

# UCH

## UCH Series Coin Hopper

ICT launches new UCH hopper with enhanced reliability and robust design. UCH is equipped with advanced micro processor which is fully compatible with ccTalk AES interface to fulfill market requirement. Single hardware design of UCH hopper can accept wide range of different coin sizes, and also help reduce inventory.

### Specifications



#### Interface

ccTalk  
ccTalk AES  
Pulse  
Hopper  
Red Flag



#### Power Consumption

Standby:  $\leq 50\text{mA}$ , 1.2W  
Operation:  $\leq 750\text{mA}$ , 18W  
Maximum:  $\leq 3\text{A}$ , 72W



#### Dispensing Speed

Max. 6 coins/second



#### Dimension

(L)154 x (W)139.2 x (H)155 mm/  
(L) 6.1 x (W) 5.5 x (H) 6.1 inches



#### Applicable Coin Size

Diameter: 20mm – 28mm  
Thickness: 1.6mm – 3.2mm



#### Weight

Approx. 800g



#### Coin Capacity

ca. 400 coins (1€)



#### Accessory

Vertical Extensions  
Capacity: 400 coins  
Height: 80 mm



#### Coin Quantity Detection

Optical Empty Sensor  
(2 adjustable positions)  
Optical Full Sensor  
(2 adjustable positions)



#### Environmental

Operating Temperature:  
5°C/41°F~50°C/122°F  
Storage Temperature:  
-30°C/-22°F~70°C/158°F  
Humidity: 30%~85%RH  
(no condensation)



#### Power Source




12V DC $\pm 10\%$   
24V DC $\pm 10\%$



#### Recommended Applications

Gaming/Amusement

Specifications are subject to change without prior notice.



### International Currency Technologies

No.28, Ln. 15, Sec. 6, Minquan E. Rd., Neihu Dist., Taipei City 114, Taiwan

Phone: +886-2-2793-1236

Fax: +886-2-2793-6125

Email: sales@ictgroup.com.tw (Product Information)

fae@ictgroup.com.tw (Technical Service)

Website: www.ictgroup.com.tw