XBA

Bill Acceptor

- Unique wide-angle banknote insertion technology
- High immunity against strong ambient light
- Advanced optical/mechanical anti-fishing structure
- Convenient firmware upgrade via USB flash drive
- MDB-FTL firmware upgrade available
- Auto-calibration technology and multi-color optical sensor
- Superior validation M.T.B.F. 750,000 cycles
- Strong resistance to severe weather conditions



Bill Acceptor

The XBA Bill Acceptor is equipped with innovative wide-angle banknote insertion technology to offer a superior acceptance rate of 98% or higher. With an outstanding design, the XBA has the ability to provide a very high degree of immunity to strong ambient light, and the advanced optical/mechanical anti-fishing structure for better investment protection. The built-in USB port allows convenient firmware upgrades via USB flash drive.

Specifications



Acceptance Rate

98% or greater



Bill Insertion

Four-way



Bill Width Accepted

62~77 mm/ 2.44~3.03 inches



Acceptance Speed

Approx. 2.5 sec. to cash box



MTBF

Validation M.T.B.F. 750,000 cycles



Capacity

Approx. 200 notes cashbox Approx. 400 notes cashbox Approx. 600 notes cashbox

Approx. 1000 notes cashbox



Interface

Pulse MDB ICT Protocol ccNet JPSTD ccTalk RS232 A0



Power Source

12V DC±10% 24V DC±10% 24V/34V DC±10% 24V AC±10%



Power Consumption

Standby: 0.15A, 1.8W Operation: 1.0A, 12W Maximum: 2A, 24W



Dimension

200-note cashbox:

104x238x115mm/ 4.09x9.37x4.53 inches **400-note cashbox**:

104x238x147mm/ 4.09x9.37x5.79 inches

600-note cashbox:

104x238x180mm/ 4.09x9.37x7.0 inches

1000-note cashbox:

104x238x255mm/ 4.09x9.37x10.0 inches



Weigh

Approx. 1.5 KG/3.31 lbs



Environmental

Operating Temperature:

-20°C/-4°F~ 60°C/140°F

Storage Temperature:

-30°C/-22°F~ 70°C/158°F Humidity: 30%~95%RH (no condensation)



Recommended Applications

Indoor/Outdoor Vending, KIOSK

-Specifications are subject to change without prior notice.









International Currency Technologies

No.28, Ln. 15, Sec. 6, Minquan E. Rd., Neihu Dist., Taipei City 114, Taiwan Phone: +886-2-2793-1236

Fax: +886-2-2793-6125

EMail: sales@ictgroup.com.tw (Product Information) fae@ictgroup.com.tw (Technical Service) Website: www.ictgroup.com.tw