

A7/V7-CAD3

A7/V7 Option Switch Settings(Pulse/Out of Service/ICT002)

Supported bill Can\$ 5, 10, 20, 3bills.

A7/V7 dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4	
★ Reject Can\$ 5	ON												
★ Accept Can\$ 5	OFF												
★ Reject Can\$ 10		ON											
★ Accept Can\$ 10		OFF											
★ Reject Can\$ 20			ON										
★ Accept Can\$ 20			OFF										
★ Reserved				ON									
★ Reserved				OFF									
★ Reserved					ON								
★ Reserved					OFF								
★ Reserved						ON							
★ Reserved						OFF							
★ Pulse Mode	ICT Mode												
★ Harness disable			Setting to OFF				ON						
★ Harness enable			Setting to OFF				OFF						
★ Inhibit Active High			Setting to OFF					ON					
★ Inhibit Active Low			Setting to OFF					OFF					
★ 1 pulse / Can\$ 1									OFF	OFF			
★ 2 pulses / Can\$ 1									ON	OFF			
★ 4 pulses / Can\$ 1									OFF	ON			
★ 20 pulses / Can\$ 1									ON	ON			
★ Pulse Speed	50ms LO / 50ms HI								OFF	OFF			
	60ms LO / 300ms HI								ON	OFF			
	30ms LO / 50ms HI								OFF	ON			
	150ms LO / 150ms HI								ON	ON			

◆ Factory configuration has all switches in the OFF position.

Note : (1) Reset the bill acceptor after setting the dip switch.

(2) SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

A7/V7-CAD3(Pulse/Out of Service/ICT002)

A7/V7 Interface Settings: 2 (Pulse)

INTERFACE	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
★ Credit-Pulse Normal LOW	OFF			
★ Pulse Mode		ON		
★ RS232 Interface		OFF		
★ Reserved			ON	
			OFF	
				ON
				OFF

★ Manufacture setting

A7/V7 Interface Settings: 3 (RS232)

INTERFACE	SW1	SW2	SW3	SW4
★ Reserved	ON			
★ Reserved	OFF			
★ Pulse Mode		ON		
★ RS232 Interface		OFF		
★ Reserved			ON	
			OFF	
				ON
				OFF

★ Manufacture setting

V7 Interface Settings: 2 (Pulse)

INTERFACE	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
★ Credit-Pulse Normal LOW	OFF			
★ Pulse Mode		ON		
★ MDB Interface		OFF		
★ Reserved			ON	
			OFF	
				ON
				OFF

★ Manufacture setting

V7 Interface Settings: 3 (MDB)

INTERFACE	SW1	SW2	SW3	SW4
★ Reserved	ON			
★ Reserved	OFF			
★ Pulse Mode		ON		
★ MDB Interface		OFF		
★ Reserved			ON	
			OFF	
				ON
				OFF

★ Manufacture setting

Currency Assign Data

Interface Bill value	Pulse	MDB
BV1	Can\$ 5	Can\$ 5
BV2	Can\$ 10	Can\$ 10
BV3	Can\$ 20	Can\$ 20