

A7/V7 Option Switch Settings

Supported bill C\$ 10(99,02), 20(99, 02, 06), 50(01, 06), 100(97, 99, 06)

A7/V7 dip-switch settings and functions:

4bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
Reject C\$ 10	ON											
Accept C\$ 10	OFF											
Reject C\$ 20		ON										
Accept C\$ 20		OFF										
Reject C\$ 50			ON									
Accept C\$ 50			OFF									
Reject C\$ 100				ON								
Accept C\$ 100				OFF								
Reserved					ON							
Reserved					OFF							
Reserved						ON						
Reserved						OFF						
Harness Disable							ON					
Harness Enable							OFF					
Inhibit Active High								ON				
Inhibit Active Low								OFF				
1 pulse / C\$ 10									OFF	OFF		
2 pulse / C\$ 10									ON	OFF		
4 pulse / C\$ 10									OFF	ON		
20 pulse / C\$ 10									ON	ON		
Pulse Speed	50ms on / 50ms off										OFF	OFF
	60ms on / 300ms off										ON	OFF
	30ms on / 50ms off										OFF	ON
	150ms on / 150ms off										ON	ON

◆ Factory configuration has all switches in the OFF position.

Note : (1) Reset the bill acceptor after setting the dip switch.

(2) SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

A7 Interface Settings: 2

	INTERFACE	SW1	SW2	SW3	SW4
★	Credit-Pulse Normal HIGH	ON			
	Credit-Pulse Normal LOW	OFF			
	Pulse Mode		ON		
★	RS232 Interface		OFF		
	HOLD			ON	
				OFF	
					ON
					OFF

V7 Interface Settings: 3

	INTERFACE	SW1	SW2	SW3	SW4
	HOLD	ON			
		OFF			
	Pulse Mode		ON		
★	MDB Interface		OFF		
	HOLD			ON	
				OFF	
					ON
					OFF