

## L70+/L70F-NIO7

### L70+/L70F/P5 DIP SWITCHES SETTING : 1(Pulse/RS232 A0/Parallel A1)

Supported bill C\$ 10, 20, 50, 100, 200, 500, 1000 7bills.

|   | FUNCTION                                                         | SW1 | SW2 | SW3 | SW4 | SW5 | SW6 | SW7 | SW8 | SW9 | SW10 |
|---|------------------------------------------------------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|
| ★ | 1 Pulse / C\$ 10                                                 | OFF | OFF | OFF |     |     |     |     |     |     |      |
|   | 2 Pulses / C\$ 10                                                | OFF | OFF | ON  |     |     |     |     |     |     |      |
|   | 3 Pulses / C\$ 10                                                | OFF | ON  | OFF |     |     |     |     |     |     |      |
|   | 4 Pulses / C\$ 10                                                | OFF | ON  | ON  |     |     |     |     |     |     |      |
|   | 5 Pulses / C\$ 10                                                | ON  | OFF | OFF |     |     |     |     |     |     |      |
|   | 10 Pulses / C\$ 10                                               | ON  | OFF | ON  |     |     |     |     |     |     |      |
|   | 20 Pulses / C\$ 10                                               | ON  | ON  | OFF |     |     |     |     |     |     |      |
|   | 100 Pulses / C\$ 10                                              | ON  | ON  | ON  |     |     |     |     |     |     |      |
|   | Fast output Pulse (Lo=50ms/ Hi=100ms)<br>/ IGT(Lo=20ms/ Hi=20ms) |     |     |     | ON  |     |     |     |     |     |      |
| ★ | Slow output (Lo=50ms/ Hi=300ms)<br>/ IGT(Lo=20ms/ Hi=20ms)       |     |     |     | OFF |     |     |     |     |     |      |
|   | Inhibit level Active Low                                         |     |     |     |     | ON  |     |     |     |     |      |
| ★ | Inhibit level Active High                                        |     |     |     |     | OFF |     |     |     |     |      |
| ★ | Accept C\$ 10 & 20                                               |     |     |     |     |     | ON  |     |     |     |      |
|   | Reject C\$ 10 & 20                                               |     |     |     |     |     | OFF |     |     |     |      |
| ★ | Accept C\$ 50 & 100                                              |     |     |     |     |     |     | ON  |     |     |      |
|   | Reject C\$ 50 & 100                                              |     |     |     |     |     |     | OFF |     |     |      |
| ★ | Accept C\$ 200                                                   |     |     |     |     |     |     |     | ON  |     |      |
|   | Reject C\$ 200                                                   |     |     |     |     |     |     |     | OFF |     |      |
| ★ | Accept C\$ 500                                                   |     |     |     |     |     |     |     |     | ON  |      |
|   | Reject C\$ 500                                                   |     |     |     |     |     |     |     |     | OFF |      |
| ★ | Accept C\$ 1000                                                  |     |     |     |     |     |     |     |     |     | ON   |
|   | Reject C\$ 1000                                                  |     |     |     |     |     |     |     |     |     | OFF  |

★ Manufacture setting

Note: (1) Please reset the bill acceptor after any changes on Dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

## L70+/L70F-NIO7(Pulse/RS232 A0/Parallel A1)

### DIP SWITCHES SETTING : 2(Pulse) Currency Assign Data

|   | FUNCTION                 | SW1 | SW2 | SW3 | SW4 |
|---|--------------------------|-----|-----|-----|-----|
| ★ | Credit-Pulse Normal HIGH | ON  |     |     |     |
|   | Credit-Pulse Normal LOW  | OFF |     |     |     |
| ★ | Pulse Mode               |     | ON  | OFF |     |
|   | RS232 A0 Mode            |     | OFF | OFF |     |
|   | Parallel A1 Mode         |     | OFF | ON  |     |
|   | Reserved                 |     | ON  | ON  |     |
| ★ | Reserved                 |     |     |     | ON  |
|   |                          |     |     |     | OFF |

★ Manufacture setting

| Interface<br>Bill value | Parallel A1 | Pulse    | RS232 A0 |
|-------------------------|-------------|----------|----------|
| BV1                     | C\$ 10      | C\$ 10   | C\$ 10   |
| BV2                     | C\$ 20      | C\$ 20   | C\$ 20   |
| BV3                     | C\$ 50      | C\$ 50   | C\$ 50   |
| BV4                     | C\$ 100     | C\$ 100  | C\$ 100  |
| BV5                     | C\$ 200     | C\$ 200  | C\$ 200  |
| BV6                     | C\$ 500     | C\$ 500  | C\$ 500  |
| BV7                     | C\$ 1000    | C\$ 1000 | C\$ 1000 |

### DIP SWITCHES SETTING : 2(RS232 A0)

|   | FUNCTION         | SW1 | SW2 | SW3 | SW4 |
|---|------------------|-----|-----|-----|-----|
| ★ | Reserved         | ON  |     |     |     |
|   |                  | OFF |     |     |     |
|   | Pulse Mode       |     | ON  | OFF |     |
| ★ | RS232 A0 Mode    |     | OFF | OFF |     |
|   | Parallel A1 Mode |     | OFF | ON  |     |
|   | Reserved         |     | ON  | ON  |     |
| ★ | Reserved         |     |     |     | ON  |
|   |                  |     |     |     | OFF |

★ Manufacture setting

| RS232 A0 INFORMATION<br>BillType Data |              |
|---------------------------------------|--------------|
| Code                                  | Denomination |
| 1                                     | C\$ 10       |
| 2                                     | C\$ 20       |
| 3                                     | C\$ 50       |
| 4                                     | C\$ 100      |
| 5                                     | C\$ 200      |
| 6                                     | C\$ 500      |
| 7                                     | C\$ 1000     |
| 8                                     | Reserved     |
| 9                                     | Reserved     |

### DIP SWITCHES SETTING : 2(Parallel A1)

|   | FUNCTION         | SW1 | SW2 | SW3 | SW4 |
|---|------------------|-----|-----|-----|-----|
| ★ | Reserved         | ON  |     |     |     |
|   |                  | OFF |     |     |     |
|   | Pulse Mode       |     | ON  | OFF |     |
|   | RS232 A0 Mode    |     | OFF | OFF |     |
| ★ | Parallel A1 Mode |     | OFF | ON  |     |
|   | Reserved         |     | ON  | ON  |     |
| ★ | Reserved         |     |     |     | ON  |
|   |                  |     |     |     | OFF |

★ Manufacture setting