



ARA6

L70/P5 DIP SWITCHES SETTING : 1(Pulse/RS232 A0)

Supported bill ARA 2, 5, 10, 20, 50, 100 6bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / ARA 1	OFF	OFF	OFF							
	2 Pulses / ARA 1	OFF	OFF	ON							
	3 Pulses / ARA 1	OFF	ON	OFF							
	4 Pulses / ARA 1	OFF	ON	ON							
	5 Pulses / ARA 1	ON	OFF	OFF							
	10 Pulses / ARA 1	ON	OFF	ON							
	20 Pulses / ARA 1	ON	ON	OFF							
	100 Pulses / ARA 1	ON	ON	ON							
	Fast output Pulse <small>Lo= 50ms Hi=100ms</small>				ON						
★	Slow output Pulse <small>Lo= 50ms Hi=300ms</small>				OFF						
	Inhibit level Active Low				ON						
★	Inhibit level Active High				OFF						
★	Accept ARA 2 & 5					ON					
	Reject ARA 2 & 5					OFF					
★	Accept ARA 10						ON				
	Reject ARA 10						OFF				
★	Accept ARA 20							ON			
	Reject ARA 20							OFF			
★	Accept ARA 50								ON		
	Reject ARA 50								OFF		
★	Accept ARA 100									ON	
	Reject ARA 100									OFF	

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

L70-ARA6(Pulse/RS232 A0)

DIP SWITCHES SETTING : 2(Pulse)

	FUNCTION	SW1	SW2	SW3	SW4
★	Credit-Pulse Normal HIGH	ON			
	Credit-Pulse Normal LOW	OFF			
★	Pulse Mode		ON		
	RS232 A0 Protocol Mode		OFF		
★	Reserved			ON	
				OFF	
					ON
★					OFF

★ Manufacture setting

DIP SWITCHES SETTING : 2(RS232 A0)

	FUNCTION	SW1	SW2	SW3	SW4
★	Reserved	ON			
		OFF			
	Pulse Mode		ON		
★	RS232 A0 Protocol Mode		OFF		
★	Reserved			ON	
				OFF	
					ON
★					OFF

★ Manufacture setting