



# BOB5

## L70/P5 DIP SWITCHES SETTING : 1(Pulse/RS232 A0/Parallel A1)

Supported bill \$b 10, 20, 50, 100, 200 5bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★ 1 Pulse / \$b 10	OFF	OFF	OFF							
2 Pulses / \$b 10	OFF	OFF	ON							
3 Pulses / \$b 10	OFF	ON	OFF							
4 Pulses / \$b 10	OFF	ON	ON							
5 Pulses / \$b 10	ON	OFF	OFF							
10 Pulses / \$b 10	ON	OFF	ON							
20 Pulses / \$b 10	ON	ON	OFF							
100 Pulses / \$b 10	ON	ON	ON							
FAST OUTPUT PULSE(LO=50ms/HI=100ms) Parallel A1(LO=20ms/HI=20ms)				ON						
★ SLOW OUTPUT PULSE(LO=50ms/HI=300ms) Parallel A1(LO=20ms/HI=20ms)				OFF						
Inhibit level Active Low					ON					
★ Inhibit level Active High					OFF					
★ Accept \$b 10						ON				
Reject \$b 10						OFF				
★ Accept \$b 20							ON			
Reject \$b 20							OFF			
★ Accept \$b 50								ON		
Reject \$b 50								OFF		
★ Accept \$b 100									ON	
Reject \$b 100									OFF	
★ Accept \$b 200										ON
Reject \$b 200										OFF

★ Manufacture setting

Note: (1) Please reset the bill acceptor after any changes on Dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

## L70-BOB5/P5(Pulse/RS232 A0/Parallel A1)

### DIP SWITCHES SETTING : 2(Pulse)

FUNCTION	SW1	SW2	SW3	SW4
★ Pulse Normal High	ON			
Pulse Normal Low	OFF			
★ Pulse Mode		ON	OFF	
RS232 A0 Mode		OFF	OFF	
Parallel A1 Mode		OFF	ON	
Reserved				ON
★				OFF

★ Manufacture setting

### DIP SWITCHES SETTING : 3(RS232 A0)

FUNCTION	SW1	SW2	SW3	SW4
★ Reserved	ON			
	OFF			
Pulse Mode		ON	OFF	
★ RS232 A0 Mode		OFF	OFF	
Parallel A1 Mode		OFF	ON	
Reserved				ON
★				OFF

#### RS232 A0 INFORMATION

BillType Data	
Code	Denomination
1	\$b 10
2	\$b 20
3	\$b 50
4	\$b 100
5	\$b 200
6	Reserved
7	Reserved
8	Reserved
9	Reserved

★ Manufacture setting

### DIP SWITCHES SETTING : 4(Parallel A1)

FUNCTION	SW1	SW2	SW3	SW4
★ Reserved	ON			
	OFF			
Pulse Mode		ON	OFF	
RS232 A0 Mode		OFF	OFF	
★ Parallel A1 Mode		OFF	ON	
Reserved				ON
★				OFF

★ Manufacture setting