

CLP5

L70/P5 DIP SWITCHES SETTING : 1(Pulse/RS232 A0)

Supported bill Ch\$ 1000, 2000, 5000, 10000, 20000 5bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★ 1 Pulse / Ch\$ 1000	OFF	OFF	OFF							
2 Pulses / Ch\$ 1000	OFF	OFF	ON							
3 Pulses / Ch\$ 1000	OFF	ON	OFF							
4 Pulses / Ch\$ 1000	OFF	ON	ON							
5 Pulses / Ch\$ 1000	ON	OFF	OFF							
10 Pulses / Ch\$ 1000	ON	OFF	ON							
20 Pulses / Ch\$ 1000	ON	ON	OFF							
100 Pulses / Ch\$ 1000	ON	ON	ON							
Fast output Pulse <small>Lo= 50ms Hi=100ms</small>				ON						
★ Slow output Pulse <small>Lo= 50ms Hi=300ms</small>				OFF						
Inhibit level Active Low					ON					
★ Inhibit level Active High					OFF					
★ Accept Ch\$ 1000						ON				
Reject Ch\$ 1000						OFF				
★ Accept Ch\$ 2000							ON			
Reject Ch\$ 2000							OFF			
★ Accept Ch\$ 5000								ON		
Reject Ch\$ 5000								OFF		
★ Accept Ch\$ 10000									ON	
Reject Ch\$ 10000									OFF	
★ Accept Ch\$ 20000										ON
Reject Ch\$ 20000										OFF

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.
(2) Dip switches 1 to 5 are only used for pulse protocol.

L70-CLP5/P5(Pulse/RS232 A0)

DIP SWITCHES SETTING : 2(Pulse)

FUNCTION	SW1	SW2	SW3	SW4
★ Pulse Normal High	ON			
Pulse Normal Low	OFF			
★ Pulse Mode		ON		
RS232 A0 Interface Mode		OFF		
★ Reserved			ON	
			OFF	
				ON
				OFF

★ Manufacture setting

DIP SWITCHES SETTING : 2(RS232 A0)

FUNCTION	SW1	SW2	SW3	SW4
★ Reserved	ON			
	OFF			
Pulse Mode		ON		
★ RS232 A0 Interface Mode		OFF		
★ Reserved			ON	
			OFF	
				ON
				OFF

★ Manufacture setting

RS232 A0 INFORMATION

BillType Data	
Code	Denomination
1	Reserved
2	Reserved
3	Reserved
4	Ch\$ 1000
5	Ch\$ 2000
6	Ch\$ 5000
7	Ch\$ 10000
8	Ch\$ 20000

Currency Assign Data

Interface Bill value	Pulse	RS232 A0
BV1	Ch\$ 1000	Ch\$ 1000
BV2	Ch\$ 2000	Ch\$ 2000
BV3	Ch\$ 5000	Ch\$ 5000
BV4	Ch\$ 10000	Ch\$ 10000
BV5	Ch\$ 20000	Ch\$ 20000