



# COP6

## L70/P5 DIP SWITCHES SETTING : 1(Pulse/RS232 A0)

Supported bill Col\$ 1000, 2000, 5000, 10000, 20000, 50000  
6bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★ 1 Pulse / Col\$ 1000	OFF	OFF	OFF							
2 Pulses / Col\$ 1000	OFF	OFF	ON							
3 Pulses / Col\$ 1000	OFF	ON	OFF							
4 Pulses / Col\$ 1000	OFF	ON	ON							
5 Pulses / Col\$ 1000	ON	OFF	OFF							
10 Pulses / Col\$ 1000	ON	OFF	ON							
20 Pulses / Col\$ 1000	ON	ON	OFF							
100 Pulses / Col\$ 1000	ON	ON	ON							
Fast output Pulse <small>Lo= 50ms Hi=100ms</small>				ON						
★ Slow output Pulse <small>Lo= 50ms Hi=300ms</small>				OFF						
Inhibit level Active Low					ON					
★ Inhibit level Active High					OFF					
★ Accept Col\$ 1000 & 2000						ON				
Reject Col\$ 1000 & 2000						OFF				
★ Accept Col\$ 5000							ON			
Reject Col\$ 5000							OFF			
★ Accept Col\$ 10000								ON		
Reject Col\$ 10000								OFF		
★ Accept Col\$ 20000									ON	
Reject Col\$ 20000									OFF	
★ Accept Col\$ 50000										ON
Reject Col\$ 50000										OFF

★ Manufacture setting

Note: (1)Please reset the bill acceptor after set the dip switch.

(2)Dip switches 1 to 5 are only used for pulse protocol.

## L70-COP6(Pulse/RS232 A0)

### DIP SWITCHES SETTING : 2(Pulse)

FUNCTION	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
Credit-Pulse Normal LOW	OFF			
★ Pulse Mode		ON		
RS232 A0 Protocol Mode		OFF		
★ Reserved			ON	
			OFF	
				ON
★				OFF

★ Manufacture setting

### DIP SWITCHES SETTING : 2(RS232 A0)

FUNCTION	SW1	SW2	SW3	SW4
Reserved	ON			
	OFF			
Pulse Mode		ON		
★ RS232 A0 Protocol Mode		OFF		
★ Reserved			ON	
			OFF	
				ON
★				OFF

★ Manufacture setting